

PRODUCT INFORMATION

ECOSE® CONCRETE FORM OIL

ECOSE® Concrete Form Oil is a ready-to-use concrete form releasing oil specially formulated from light viscosity mineral oil and a proprietary additive system that ensures excellent separation from wood, metal and plastic forms. **ECOSE® Concrete Form Oil** is non-staining and resists water wash-off while providing rust protection to metal forms.

FEATURES AND BENEFITS:

- ✓ **Non Staining**
- ✓ **Ready to Use**
- ✓ **Prevents Concrete Build Up on Forms**
- ✓ **Use on Metal, Plastic and Wood Forms**
- ✓ **All Seasons Use**
- ✓ **Low VOC Content**
- ✓ **Prevents Rusting of Metal Forms**
- ✓ **Prevents Buildup of Concrete on Forms**

APPLICATIONS:

ECOSE® Concrete Form Oil is designed to impart easy of separation on wood, steel, aluminum, epoxy coated and other types of forms in both indoor and outdoor conditions. This high quality form oil may be easily applied with a roller, brush, or sprayer. **ECOSE® Concrete Form Oil** provides typical coverage of 700–900 sq ft. /gal when properly applied. The applied film should be uniform and completely wet the surface. For best results, this product should be applied to a clean, dry surface. **ECOSE® Concrete Form Oil** has proven to increase the life of both wood and metal forms by preventing concrete build-up.

Typical Properties

Product Code	Test Method	535705
Viscosity, cSt @ 40°C	ASTM D445	19.4
Viscosity, cSt @ 100°C	ASTM D445	4.1
Color	ASTM D1500	L1.0
Pour Point, °F (°C)	ASTM D97	-30 (-34)
Flash Point, COC, °F (°C)	ASTM D92	380 (193)
VOC content, g/L	ASTM D3960	<50
Density	ASTM D4052	7.19
Application Rate, typical	Sq./ft - gallon	700 (wood)
	Sq./ft - gallon	900 (metal)

AVAILABILITY:

ECOSE® Concrete Form Oil is available throughout Nu-Tier Brands’ marketing area. Your Nu-Tier representative can provide specific information. Need additional information? Call Nu-Tier Brands @ 1-877-771-LUBE (5823) or visit www.nu-tierbrands.com.