

PRODUCT INFORMATION

ECOSE[®] ANTI-RUST EP

Extended Protection

ECOSE[®] Anti-Rust EP is a solvent-cutback petroleum compound designed for use with both ferrous and non-ferrous metals. It forms an extended protective coating upon evaporation of the solvent. See reverse side for recommended application temperatures.

FEATURES AND BENEFITS:

ECOSE[®] Anti-Rust EP has unique water displacing characteristics. Additionally, it forms a thin film of protection, providing superior metal surface protection. It provides a coating that will not crack or peel when exposed to a wide range of ambient temperatures.

APPLICATIONS:

ECOSE[®] Anti-Rust EP is recommended for steel surfaces in a variety of applications including machinery, tools, automotive components, marine hardware, construction equipment and any metal surface requiring a protective coating for storage. It is applied by dipping, spraying or brushing at normal room temperatures. It is removed by petroleum solvents or conventional degreasing methods. Safety precautions should be observed in handling this product due to the solvent content.

Typical Properties

Product Code	Test Method	535381
Viscosity, cSt @ 40°C	ASTM D-445	2.5
Viscosity, SUS @100°F	ASTM D-2161	34
Film Type		Transparent, oily
Color		DARK
Flash Point, COC, °F °C	ASTM D-92	160° F (72°C)
Water Displacement	MIL-C-16173D	PASS
Salt Spray (5%) Hours to Failure, AVG		55
Humidity Cabinet Test, Hours Polished Panels Sandblasted Panels	ASTM D-1748	1440+ 1440+
Application Temperature, °F		40-90
Normal Protection Term, Months Indoor Outdoor, sheltered		10-12 3-4

AVAILABILITY:

ECOSE[®] Anti-Rust EP is available throughout Nu-Tier Brand’s marketing area. Your Nu-Tier representative can provide specific information. Need additional information? Call Nu-Tier Brands @ 1-877-771-LUBE (5823) or visit Nu-tierbrands.com.