

PRODUCT INFORMATION

ECOSE[®] MULTI-PURPOSE ATF D/M

ECOSE[®] Multi-Purpose ATF D/M is a high quality automatic transmission fluid formulated with premium base stocks and advanced additive technology. It is designed for use in electronic and hydraulic controlled transmissions and can also be used in certain other applications such as power steering units, rotary screw compressors, & some hydraulic fluid applications:

FEATURES AND BENEFITS:

ECOSE[®] Multi-Purpose Automatic Transmission Fluid D/M provides the following benefits:

- Excellent wear protection
- Good anti-foam properties
- Red color for easy identification
- Outstanding oxidation resistance
- Protection against rust and corrosion
- Very good low temperature performance providing good cold-start shifting
- Superior frictional characteristics for smooth shifting

APPLICATIONS:

ECOSE[®] Multi-Purpose ATF D/M is recommended for pre-2006 model General Motors automatic transmissions where a now obsolete DEXRON[®] III fluid is specified and post-1981 and pre-2007 Ford automatic transmissions where a now obsolete MERCON[®] fluid is specified. **Not for use in applications calling for DEXRON[®] VI or MERCON[®] V fluids** or in select transmission applications requiring specialized fluids. It is suitable for use where Allison C-4 and Caterpillar TO-2 fluids are required. Additionally, this product is suitable for use in the following applications:

- In powershift transmissions, torque converters and hydrostatic transmissions
- In some hydraulic and compressor systems where excellent low-temperature fluidity and anti-wear properties are required.

Always consult the equipment owner's manual for proper fluid selection.

AVAILABILITY:

ECOSE[®] Multi-Purpose ATF D/M is available throughout Nu-Tier Brands' marketing area. Your Nu-Tier representative can provide specific information. Need additional information? Call Nu-Tier Brands @ 1-877-771-LUBE (5823) or visit Nu-tierbrands.com.

ECOSE[®] Multi-Purpose Automatic Transmission Fluid D/M

Typical Properties

Product Code		532022
	Test Method	
API Gravity	ASTM D-1298	32.8
Specific Gravity	ASTM D-4052	0.861
Viscosity, cSt @ 40°C	ASTM D-445	34.3
Viscosity, cSt @ 100°C	ASTM D-445	7.1
Viscosity Index (min)	ASTM D-2270	168
Brookfield Viscosity, cP @ -40°C	ASTM D-2983	17,250
Brookfield Viscosity, cP @ -20°C	ASTM D-2983	1,075
Flash Point, °C (°F)		218 (424)
Pour Point, (°F)	ASTM D-5949	-46
Color	ASTM D-1500	Red
Environmental Performance		