



# Product Bulletin

## GULFSOL<sup>®</sup>

**Gulfsol<sup>®</sup>** is a Type-3 regular mineral spirits as defined by ASTM D-235. This solvent is a hydrotreated, desulfurized, narrow-cut fraction of heavy naphtha. It is often referred to as 'Regular Mineral Spirit Solvent' or 'Stoddard Solvent'.

### FEATURES AND BENEFITS:

**Gulfsol<sup>®</sup>** is a versatile fluid for use in various applications. It is an excellent isoparaffinic hydrocarbon solvent for product dilution or cleaning applications. It is made from a petroleum distillate stream containing a blend of C9 to C12 hydrocarbons. It is extensively refined to help eliminate odor producing components.

### APPLICATIONS:

**Gulfsol<sup>®</sup>** can be used in a multitude of industrial applications that require the characteristics of narrow-cut naphtha for solvent-based products. Some typical examples include paints and coatings, industrial dry cleaning, waterless hand cleaners, lacquer thinners, asphalt cutback, diluents, degreasers, and general solvent cleaners.

### AVAILABILITY:

**Gulfsol<sup>®</sup>** is available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853) or visit [Nu-tierbrands.com](http://Nu-tierbrands.com).

### Typical Properties

Product Code	Test Method	380033
Flash Point, °F (TCC)	ASTM D-56	135
Boiling Point, °F	ASTM D-86	380
Dry Point, °F	ASTM D-86	410
Specific Gravity, API, @ 60°F	ASTM D-4052	0.802
Appearance	Visual	Clear Liquid
Odor	ASTM D-1296	Mild odor
Kauri-Butanol Value	ASTM D-1133	34
Aeromatics, %	ASTM D-3257	0.1
Color, Saybolt	ASTM D-156	+30
Copper Corrosion, 3 hr, 212°F	ASTM D-130	1
Pour Point, °F	ASTM D-97	<-94
Avg Molecular Weight	API	158

*\*Note: Values shown are typical only and do not constitute a specification. Minor variations in product are to be expected in normal manufacturing. Always confirm with the original manufacturer's recommendation for proper equipment operating requirements.*