



# Product Bulletin

## GULFLEX<sup>®</sup> 5% MOLY EP GREASE

**Gulflex<sup>®</sup> 5% Moly EP Grease** is a heavy-duty, high performance, extreme pressure (EP) grease fortified with 5% molybdenum disulfide (MoS<sub>2</sub>, commonly referred to as “moly”) to meet Caterpillar’s Multipurpose Molybdenum Grease (MPGM) requirements. It is primarily intended for agricultural, mining, and construction equipment applications, as well as most heavy-duty industrial applications requiring protection from heavy shock loading situations. The presence of moly provides reserve protection in these situations which helps to prevent metal-to-metal contact and costly equipment downtime. The presence of moly is also valuable in unclean environments or when proper re-greasing intervals are not followed.

### FEATURES AND BENEFITS:

**Gulflex<sup>®</sup> 5% Moly EP Grease** utilizes a lithium complex thickener system compounded with premium heavy duty paraffinic base oils to provide excellent mechanical and structural stability. The grease is characterized by its high dropping point (above 500°F) and is formulated with a state-of-the-art additive package to provide superior rust and corrosion protection, good low temperature pumpability and resistance to water washout. The base oil, thickener, and additive components of **Gulflex<sup>®</sup> 5% Moly EP Grease** have been specifically selected for their performance enhancements under wet, muddy, slow-speed, high temperature, high load, and heavy-shock load conditions like those encountered in off-road and general construction service. Additionally, it meets the requirements for the following:

- Mack MG-C
- Caterpillar MPGM

### APPLICATIONS:

**Gulflex<sup>®</sup> 5% Moly EP Grease** is recommended for use in agricultural, mining, and construction equipment applications, as well as heavily loaded industrial applications that require or would benefit from a moly type grease. Typical applications in construction and agricultural equipment include virtually all lubrication grease points on earthmovers, dozers, backhoes, scrapers, cranes, shovels, etc. In addition to automotive wheel bearing and chassis lubrication, it can also be used in fifth wheels, CV joints, and universal joints. It is also particularly well-suited for heavily loaded pivot pins, spined shafts, or other surfaces subjected to sliding.

**AVAILABILITY:**

**Gulflex® 5% Moly EP Grease** is available throughout Gulf’s marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853) or visit Nu-tierbrands.com.

**Typical Properties**

<b>NLGI Grade</b>		<b>2</b>
<b>Product Code</b>	<b>Test Method</b>	343017
Thickener Type	ASTM D-128	Lithium Complex
Thickener Content, wt.%	ASTM D-128	10
Molybdenum Disulfide, wt.%	ASTM D-128	5.0
Base Oil Viscosity, cSt @ 40°C	ASTM D-445	350
Base Oil Viscosity Index	ASTM D-2270	92
Color	Visual	Gray
Appearance	Visual	Smooth
Cone Penetration, @ 77°F Worked, 60x	ASTM D-217	280
Dropping Point, °F (°C)	ASTM D-2265	525 (274)
Oil Separation, % (max.)	ASTM D-1742	6
Water Washout, wt.% loss @ 175°F	ASTM D-1284	5% max.
Rust Prevention, rating	ASTM D-1743	Pass
Four-Ball Wear Test, mm	ASTM D-2266	0.40
Four-Ball Weld Point, kgf	ASTM D-2596	620
Timken OK Load, lbs.	ASTM D-2509	55
Operating Temperature Ranges: Minimum, °F (°C) Max. Continuous Service, °F (°C)		0 (-18) 325 (163)