



Product Bulletin

ALL SEASON ANTIFREEZE & COOLANT 50/50 Prediluted

Gulf All Season 50/50 Prediluted Antifreeze & Coolant is a 50/50 blend of high quality ethylene glycol-based antifreeze and purified deionized water. Right out of the bottle, this product provides outstanding performance and protection and exceeds automobile manufacturers' requirements.

Gulf All Season 50/50 Prediluted Antifreeze & Coolant:

- Approved for use in gasoline and diesel engines
- Protects all engine metals including aluminum
- Protects against engine freeze-up and boil-over
- Meets ASTM D-4340 and ASTM D-4985 requirements
- Meets heavy duty standards for low silicate antifreeze
- 100% virgin ethylene glycol based

Product Reference:

Gulf All Season Antifreeze & Coolant 50/50 Prediluted – **Product Number 841112**

Properties	Typical Specifications	ASTM Test Method
Specific Gravity	1.07	D-1122
pH, 50% V	10.5	D-1287
Ash, Wt. %	2.5 Max	D-3634
Color	Green	-
Reserve Alkalinity	5.0 – 7.0	D-1121
Silicon, ppm	125 Max	D-6130
Bittering Agent	Yes	-
Antifreeze / Water %,50/50 Freeze Point	-34°F (-36°C)	D-1177
Antifreeze / Water %,50/50 Boil Point*	226°F (108°C)	D-1120

*With a 15 psi pressure cap

¹ Conventional formulation can be used with the addition of SCA (Supplemental Coolant Additives) in heavy duty vehicles. Consult your owner's manual for recommendations.

**Suitable Where the Following are Recommended:
¹ HEAVY DUTY <ul style="list-style-type: none"> • Caterpillar • Cummins 90T8-4 • GM 1899M • John Deere H24B,C • Mack Truck • Navistar B1 • SAE J1941 • TMC RP 302B • Volvo/GM Heavy Truck
AUTOMOTIVE <ul style="list-style-type: none"> • ASTM D 3306 • ASTM 4985 • Chrysler MS 7170 • Ford ESE-M97B44-A • GM 1825M • SAE J1034

**Meets performance requirements but may or may not meet certain chemical requirements.

AVAILABILITY:

Gulf All Season Antifreeze & Coolant 50/50 Prediluted is available throughout Gulf Lubricants' marketing area. Your sales representative can provide specific information. Need additional information? Call Gulf Lubricants @ 1-800-566-Gulf (4853) or visit www.gulflubricants.net.