



Product Bulletin

GULF COOL ANTIFREEZE & COOLANT 50/50 PREDILUTED

Gulf Cool 50/50 Antifreeze & Coolant is a premium carboxylate-based Organic Acid Technology (OAT) ethylene glycol-based coolant that is specially formulated for use in all General Motors vehicles requiring DEX-COOL® (GM 6277M) orange –colored coolant. **Gulf Cool 50/50 Prediluted Coolant** helps prevent freeze-ups and boil-overs while providing up to 150,000 miles or 5 years of maximum protection when used with complete drain and refill. **Gulf Cool 50/50 Prediluted Antifreeze & Coolant** is recommended for use in the cooling systems of all types of automotive engines, foreign or domestic.

Product Reference:

Gulf Cool 50/50 Prediluted Antifreeze & Coolant – Product Number 841120

Features and Benefits:

- Long Service Life - 150,000 miles or 5 years cooling system protection with complete drain and refill
- Meets European phosphate free and Japanese silicate free requirements
- Excellent corrosion protection for aluminum, brass, cast iron, steel, solder, and copper
- Special inhibitors provide long term protection against damaging rust and corrosion
- Meets ASTM D 3306 for automotive service
- Meets ASTM D 4340

Properties	Typical Specifications	ASTM Test Method
Specific Gravity	1.065	D-1122
Reserve Alkalinity	2.6	D-1121
pH, 50% Volume Solution	8.4	D-1287
Color	Orange	
Foam Test, ml/sec	<50/ 3	D 1881
Bittering Agent	Yes	-
Antifreeze / Water %,50/50 Freeze Point	-34°F (-36°C)	D-1177
Antifreeze / Water %,50/50 Boil Point*	226°F (108°C)	D-1120

*With a 15 psi pressure cap.

**Meets performance requirements but may or may not meet certain chemical requirements.

**Suitable Where the Following are Recommended:
<ul style="list-style-type: none"> • ASTM D3306 • ASTM D4340 • Chrysler MS 7170 • Daimler DBL 7700 • Ford WSS-M97B44-D • GM 1825M • GM 6277M (DEX-COOL® Spec) • SAE J1034

AVAILABILITY:

Gulf Cool 50/50 Prediluted Antifreeze & Coolant is available throughout Gulf Lubricants' marketing area. Your sales representative can provide specific information. Need additional information? Call Gulf Lubricants @ 1-800-566-Gulf (4853) or visit www.gulflubricants.net .