



Product Bulletin

GULF GOLD MULTI-VEHICLE ANTIFREEZE & COOLANT 50/50 Prediluted

Gulf Gold Multi-Vehicle 50/50 Prediluted Antifreeze & Coolant can be used to top-off cooling systems filled with any automotive antifreeze including GM DEX-COOL®, Ford and Chrysler coolants. **Gulf Gold Multi-Vehicle 50/50 Prediluted Antifreeze & Coolant** does not change color when added to existing fluid and can be used to top-off any color automotive antifreeze including green, yellow, orange, fuchsia, blue and red.

When used in a complete cooling system flush and refill service along with regular specified maintenance, **Gulf Gold Multi-Vehicle 50/50 Prediluted Antifreeze & Coolant** can realize 150,000 miles or 5 years of maximum cooling system protection.

Product Reference:

Gulf Gold Multi-Vehicle 50/50 Prediluted Antifreeze & Coolant – Product Number 841132

Performance Features:

- For use in all makes and models of passenger cars and light duty trucks
- Does not change color when added to existing fluid
- Contains no phosphates, nitrites, borates, or silicates
- Extended service capable - 150,000 miles or 5 years

Properties	Typical Specifications	ASTM Test Method
Specific Gravity	1.070-1.080	D-1122
Foam Test, ml/sec	<50/3	D 1881
pH, 50% V/V	7.5-10.0	D-1287
Color	Gold	--
Water mass %	50% min.	D-1123
Bittering Agent	Yes	-
Antifreeze / Water %,50/50 Freeze Point	-34°F (-36°C)	D-1177
Antifreeze / Water %,50/50 Boil Point*	226°F (108°C)	D-1120

*With a 15 psi pressure cap

****Suitable Where the Following are Recommended :**

- ASTM D-3306, D-4340
- Chrysler MS 7170
- Chrysler MS 9769
- Ford ESE-M97B44-A,
- Ford WSS-M97B44-D
- GM 1825M
- GM 6277M (DEX-COOL®)
- Mercedes-Benz DBL 7700
- SAE J1034

**Meets performance requirements but may or may not meet certain chemical requirements.

AVAILABILITY:

Gulf Gold Multi-Vehicle 50/50 Prediluted Antifreeze and Coolant is available throughout Gulf Lubricants' marketing area. Your sales representative can provide specific information. Need additional information? Call Gulf Lubricants @ 1-800-566-Gulf (4853) or visit www.gulflubricants.net