



Product Bulletin



GULFPRIDE® PREMIUM HIGH PERFORMANCE SYNTHETIC BLEND MOTOR OIL

Gulfpride® Premium High Performance Synthetic Blend Motor Oil employs a synergistic combination of synthetic lubricants and ultra pure base oils in conjunction with latest additive technology to provide a higher performance level when compared to conventional engine oils. These **Premium High Performance** lubricants are formulated to help reduce the occurrence of oil related low speed pre-ignition (**LSPI**) and provide an increased layer of defense against turbocharger deposits often found in high torque, turbocharged gasoline direct inject (**TGDI**) engines. These oils are formulated to help provide outstanding levels of performance, cleaning power and engine protection, even during longer oil change intervals as outlined by OEM.

Gulfpride® Premium High Performance Motor Oil meets or exceeds the latest automotive manufacturers requirements and is licensed for API Service SN PLUS / ILSAC GF-5. These oils are backward serviceable for use where API SN or earlier "S" category engine oils are recommended, and optimized for use in vehicles operating on ethanol-containing fuels up to E85.

APPLICATION:

Gulfpride® Premium Synthetic Blend Motor Oil offers greater protection in turbocharged and high-power high-efficiency gasoline, propane, and natural gas engines in modern passenger car and light duty trucks.

Meets or exceeds the requirements of:

- Chrysler MS-6395 and GM6094M (obsolete speciation)
- Ford WSS-M2C945-A (SAE 5W-20), Ford WSS-M2C945-B1 (SAE 5W-20)
- Ford WSS-M2C946-B1 (SAE 5W-30), Ford WSS-M2C946-B1 (SAE 5W-30)
- Honda specification (SAE 5W-20)

Typical Properties

SAE Grade		5W-20	5W-30
Product Code	Test Method	330120	330122
Highest API/ILSAC Performance		SN PLUS / GF-5	SN PLUS / GF-5
Viscosity, cSt @ 40°C	ASTM D-445	47.5	62.0
Viscosity, cSt @ 100°C	ASTM D-445	8.5	11.0
Viscosity Index	ASTM D-2270	158	175
Color	ASTM D-1500	L3.0	L3.0
CCS @ -30°C, cP	ASTM D-5293	4200	3800
High-Temp/High-Shear Viscosity, cP @ 150°C	ASTM D-4683	2.6	3.1
Pour Point, °F	ASTM D-97	-40	-45
Flash Point, COC, °F	ASTM D-92	435	445

AVAILABILITY:

Gulfpride® Premium High Performance Synthetic Blend Motor Oil is available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF or visit Nu-tierbrands.com.