



Product Bulletin

GULF HIGH TACK BAR & CHAIN OIL

Gulf High Tack Bar & Chain Oil has been formulated to provide maximum protection over a wide temperature range. This tacky lubricant contains special additives to protect bar and chain against wear and to cling steadfastly and resist sling-off. This product has effectively been used to lubricate roller chains, slides and other equipment in the industrial and agricultural areas where cling, anti-wear performance is required.

FEATURES AND BENEFITS:

Gulf High Tack Bar & Chain Oil is fortified with tackifier to reduce dripping and sling-off. Foam inhibitors minimize product foaming, and increased anti-wear agents and detergents insure longer bar, chain and sprocket life.

- Adheres to metal parts, even at high speeds
- Helps reduce heat and friction to extend chain and bar life
- Contains special inhibitors to prevent rust and corrosion
- Low pour point provides trouble free operation over a wide temperature range

APPLICATIONS:

Gulf High Tack Bar & Chain Oil helps consolidate inventory and provides better lubrication performance for link chains (mechanical or automatic) under most climates. It is the right choice for chain saws, motorcycles, and farm equipment, as well as industrial link chains where applications require high quality bar and chain oil.

Gulf High Tack Winter Bar & Chain Oil is recommended for winter conditions when temperatures are consistently below 0°C (32°F). It provides outstanding low temperature flow properties while providing full tackiness at normal operating speeds.

Typical Properties

SAE Grade		10	30
Product Code	Test Method	335702	335704
Viscosity, cSt @ 40°C	ASTM D-445	46	90.5
Viscosity, cSt @ 100°C	ASTM D-445	7.2	10.9
Viscosity Index		117	105
Pour Point, °F	ASTM-97	-24	5
Flash Point, COC, °F	ASTM-92	420	430
Texture/Presence of Tackifier		Pass (Tacky/Stringy)	Pass (Tacky/Stringy)