



Product Bulletin

GULF VP Preservative Oil 32 *Vapor Phase Corrosion Inhibiting Properties*

Gulf VP Preservative Oil 32 is a specialized circulating and lubricating oil that exhibits outstanding rust protection. **Gulf VP 32** is formulated to provide rust protection to steel surfaces which come in contact with the oil, leaving a thin film. Its unique design also provides a rust inhibitor vapor for steel surfaces which are above the level of the oil in an enclosed space.

Benefits and Features:

- Excellent Demulsibility
- Excellent Oxidation Stability
- Leave a Thin Film After Oil is Drained
- Excellent Rust Protection for Surfaces Above Oil Level
- Extended Rust Protection for Metal Surfaces Submerged in Oil

Applications:

Gulf VP Preservative Oil 32 is recommended to protect metal surfaces against rust in engines, gear boxes and other closed systems. The **VP** (vapor phase) fills the closed spaces with a vapor that forms a monomolecular protective layer on all metal surfaces. This layer pacifies metal surfaces to prevent rust and corrosion. Because the system is sealed, the protective layer is constantly maintained. The length of time the protection continues depends on how well the system is sealed, but protection for one year or longer is generally attainable.

Typical Properties

Product Code - 335385	Test Method	
Kinematic Viscosity, cSt @40°C	ASTM D 445	32.0
Kinematic Viscosity, cSt @100°C	ASTM D 445	5.4
Viscosity Index	ASTM D 2270	100
Flash Point, COC, °F	ASTM D 92	325
Pour Point, °F	ASTM D 97	-0
Specific Gravity	ASTM D 129	0.87
Rust Test, Synthetic Sea Water	ASTM D 665	Pass
Rust Test, Distilled Water	ASTM D 665	Pass
Copper Corrosion, 3 hrs. @ 212°F	ASTM D 130	1B

AVAILABILITY: **Gulf VP Preservation Oil 32** is available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional Information? Call Gulf @ 1-800-566-GULF (4853) or visit Nu-tierbrands.com.

07/17

NU-TIER BRANDS, INC.

UNDER LICENSE FROM GULF OIL LP • TULSA, OK 74133 • Phone 918-550-8026 • www.gulflubricants.net or www.Nu-Tierbrands.com