



Product Bulletin

GULF SS TRACTOR FLUID

Gulf SS Tractor Fluid is a highly shear stable, premium multi-purpose tractor fluid formulated to exceed original equipment manufacturers (OEM) performance requirements. By combining select base oils and an advanced additive package this fluid offers exceptional resistance to viscosity loss due to shearing over conventional tractor fluids. This fluid is designed to function as a common sump fluid in a wide variety of agricultural, mining and construction equipment that requires one fluid be used to lubricate the hydraulic system, wet brake system, final drive, transmission and differential.

Gulf SS Tractor Fluid is recommended for use in modern tractors and off-highway equipment often found operating in harsh environments over a wide range of ambient temperatures. This shear stable tractor fluid is fully interchangeable with conventional universal tractor fluids, however, to obtain optimal performance it is recommended to drain old fluid and refill with new **Gulf SS Tractor Fluid**.

Gulf SS Tractor Fluid is suitable for use and meets or exceeds the following industry specifications:

AGCO Power Fluid 821XL
 Allison C-2, C-3, C-4 (Agriculture Only)
 J.I. Case MS1209, MS1207, MS1206
 Case New Holland (CNH) MAT3525, 3506, 3505
 Caterpillar TO-2
 Ford M2C134-A/B/C/D, M2C86-B, M2C53-A
 ESN-M2C41-B, M2C48-B
 International Harvester B-6 Hy-Tran®
 John Deere JDM J20A, J20C, Hy-Gard®, J14B/C (Type 303),

Kubota UDT Fluid
 Massey Ferguson CMS M1145, 1143, 1141 Permatran®III
 Oliver Type 55
 Volvo WB-101
 White Farm Equipment Q-1705, Q-1722, Q-1766B, Q-1802
 Q-1826
 ZF Transmissions TE-ML03E, 05F, 06F, 07E
 Hydraulic Mfgs: Denison HF-0, HF-1, HF-2; Vickers (Eaton)
 M-2950-S, I-286-S; Sauer-Sundstrand Hydrostatic Transmission

Gulf SS Tractor Fluid:

*Typical Properties

Product Code	Test Method	331965
Viscosity, cSt @ 40°C	ASTM D-445	60.0
Viscosity, cSt @ 100°C	ASTM D-445	9.5
Brookfield Viscosity, cP @ -34.4°C	ASTM D-2983	26,000
Viscosity Index	ASTM D-2270	145
KRL Shear Testing after 20 hrs / visc. cSt @100°C	CEC-L-45-T-93	8.2
Color	ASTM D-1500	L3.5
Pour Point, °F	ASTM D-5949	-43
Flash Point, COC, °F	ASTM D-92	410
Gravity, API	ASTM D-4052	29.8

*Typical Properties are average values only. Continual product development may change data slightly without effecting performance.