



Product Bulletin

GULF HARMONY AW 220 LV

Gulf Harmony AW 220 LV is formulated with premium medium to heavy viscosity, highly refined mineral base oils that are carefully selected for their high boiling point and low vapor pressure. These quality base oils are coupled with a unique additive system that provides long service life, thermal stability and wear protection during start-up and boundary conditions. **Gulf Harmony AW 220 LV** is designed for use in certain hydraulic pumps, positive displacement blowers, vacuum units and once-through-sealing vacuum pumps.

FEATURES AND BENEFITS:

- Excellent anti-wear protection for pumps, motors and valves
- Non-detergent and non-foaming formulation
- Rust and corrosion protection
- Very good hydrolytic stability

APPLICATIONS:

Gulf Harmony AW 220 LV is recommended for applications where a quality non-foaming, non-detergent compressor/hydraulic oil is required. It is also well suited for various large Stokes and Roots vacuum pump applications and centrifugal blowers where the equipment manufacturer requires a high viscosity, anti-wear lubricant with a high boiling range, low vapor pressure that will resist high temperature oxidation.

Typical Properties

ISO Viscosity Grade		220
Product Code	Test Method	334234
Viscosity, cSt @ 40°C	ASTM D-445	215.0
Viscosity, cSt @ 100°C	ASTM D-445	18.8
Viscosity Index	ASTM D-2270	98
Color	ASTM D-1500	L3.5
Pour Point, °F (°C)	ASTM D-5949	0 (-18)
Flash Point, COC, °F (°C)	ASTM D-92	525 (274)
Oxidation Stability, hours	ASTM D-943	2,500
API Gravity, 60°F	ASTM D-4052	29.6
Density, lbs/gal (g/L)	Calculated	7.31

AVAILABILITY:

Gulf Harmony AW 220 LV is available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF(4853) or visit Nu-tierbrands.com.