



# Product Bulletin



## GULFSOL<sup>®</sup> 140

*High Purity Paraffinic Naphthenic Solvent*

**Gulfsol<sup>®</sup> 140** is a high-purity mixture of hydrotreated isoparaffins and naphthenics with very low levels of polynuclear aromatics. It is a clear liquid with a minimum flash point specification of 142°F (Tag Closed Cup) and very mild odor.

### APPLICATIONS:

**Gulfsol<sup>®</sup> 140** may be used in a wide array of applications that include industrial and institutional cleaning, paint and coatings, water treatment, pesticide formulations, consumer products, lubricating oils, chemical process solvents, oilfield drilling fluids, degreasers, lamp oil, metal rolling oils, freeze point depressants, and more. It is extensively refined to help eliminate odor producing components.

### Typical Properties

Product Code	Test Method	380033
Distillation Range, °F	ASTM D-86	350
IBP		380
10%		400
90%		404
95%		430
EP		
Flash Point, °F (TCC)	ASTM D-56	>142
Pour Point, °F	ASTM D-97	<-94
Dry Point, °F	ASTM D-86	410
Viscosity, cSt @20°C	ASTM D-445	1.8
@40°C		1.3
Specific Gravity, API, @ 60°F	ASTM D-4052	0.800 – 0.820
Appearance	Visual	Clear Liquid
Odor	ASTM D-1296	Mild odor
Kauri-Butanol Value	ASTM D-1133	34
Aeromatics, %	ASTM D-3257	0.1
Color, Saybolt	ASTM D-156	+25
Vapor Pressure, torr @ 20°C	API, calc	0.34
Avg Molecular Weight	API	156

*\*Note: Values shown are typical only and do not constitute a specification. Actual properties may vary from lot to lot.*

### AVAILABILITY:

**Gulfsol<sup>®</sup>140** is available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-4853 or visit [www.Nu-tierbrands.com](http://www.Nu-tierbrands.com).

07/20

**NU-TIER BRANDS, INC.**

UNDER LICENSE FROM GULF OIL LP • TULSA, OK 74133 • Phone 918-550-8026 • [www.gulflubricants.net](http://www.gulflubricants.net) or [www.Nu-Tierbrands.com](http://www.Nu-Tierbrands.com)