



Product Bulletin


SUPER DUTY SELECT XFE SYNTHETIC BLEND, SEVERE DUTY, FUEL EFFICIENT

Gulf Super Duty Select XFE 10W-30 Diesel Engine Oil is premium synthetic blend diesel engine oil specifically formulated for engines operating under extreme conditions. It is formulated to help extend engine life, provide longer oil drain capability and meets or exceeds API FA-4 specification for fuel-efficient engine oils. Gulf Super Duty Select XFE 10W-30 is boosted with EXTRA performance additives that provides enhanced oxidation resistance and significant* improvement at controlling sludge wear than previous CJ-4 conventional engine oil. This advanced formulation is designed for those long haul operators that desire extended drain intervals and are operating in a heavily loaded, steady state environment.

Gulf Super Duty Select XFE 10W-30 is engineered to meet OEM performance requirements outlined by Cummins CES 20087 and Detroit Fluid Specification 93K223. Proprietary formulation delivers excellent wear protection and outstanding TBN retention.

Benefits and Features:

- Excellent cold weather starts with low temperature fluidity and pumpability
- Improved fuel economy in engines designed to operate with lower viscosity oils
- Maintain its viscosity under high-temperature/high-shear, or HTHS, conditions.



Typical Properties

Product Code - 331336	Test Method	SAE 10W-30
API Service		FA-4
Kinematic Viscosity, cSt @40°C	ASTM D 445	64.0
Kinematic Viscosity, cSt @100°C	ASTM D 445	10.5
Viscosity Index	ASTM D 2270	153
CCS @ -25°C, cP	ASTM D 5293	5,300
Pour Point, °C	ASTM D 5949	-35
Color	ASTM D 1500	L3.5
Sulfated Ash, wt%	ASTM D 92	1.0
Total Base Number, mg KOH/g	ASTM D 2896	10.0
HTHS @ 150°C, cP	ASTM D 4683	3.1

NOTE: Gulf Super Duty Select XFE 10W-30 engine oil should only be used where an API FA-4 oil is recommended by the OEM. Before using this product in an engine, users should consult recommendations as outlined in the owner's manual or other service bulletins.

*Relative performance based on results from Cummins ISM engine test run with SAE 10W-30 CJ-4, low HTHS oil.

AVAILABILITY: Gulf Super Duty Select XFE Diesel Engine Oil is available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853) or visit Nu-tierbrands.com.

01/17

NU-TIER BRANDS, INC.

UNDER LICENSE FROM GULF OIL LP • TULSA, OK 74133 • Phone 918-550-8026 • www.gulflubricants.net or www.Nu-Tierbrands.com