# C-V 40C Cutting Oil **SDS - Safety Data Sheet**

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: ECOSE® C-V 40C Cutting Oil Other means of identification: Metalworking Oil SDS Number: 535318 CAS Number: Blend CHEMTREC: 1-800-424-9300 (For emergencies) Supplier: Nu-Tier Brands, Inc. 8282 S. Memorial Dr., Suite 302 Tulsa, OK 74133 1-877-771-5823 (For Product Information) www.nu-tierbrands.com

#### 2. HAZARDS IDENTIFICATION

# **Classified Hazards**

GHS Phrases: H304 – May be fatal if swallowed and enters airways H320 - Causes eye irritation H315 – Causes skin irritation H410 - Very toxic to aquatic life with long lasting effects

GHS Precautionary Statements: P302+352 - IF ON SKIN: Wash with soap and water P305+351+338 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P273 – Avoid release to the environment


This product contains hazardous material as defined by the OSHA Hazard Communication Standard CFR 1910.1200.

## **General Precautionary Statements**

Keep out of reach of children. Wash with plenty of soap and water. Read label before use.

If medical advice is needed, have product container or label at hand.





#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS	Concentration
Hydrotreated distillate, middle	64742-46-7	0-60%
Hydrotreated petroleum oil	Various	0-40%
Sulfurized fat	Proprietary	5-15%
Chlorinated paraffin	Proprietary	5-10%
Proprietary Ingredients	Proprietary	10-25%

Any concentration shown as a range is to protect the confidentiality of formulation which is considered a trade secret.

# C-V 40C Cutting Oil SDS - Safety Data Sheet

## 4. FIRST AID MEASURES

## EYE CONTACT FIRST AID:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation occurs, get medical assistance.

#### SKIN CONTACT FIRST AID:

Wash skin with plenty of soap and water while removing contaminated clothing and shoes.

#### INHALATION FIRST AID:

IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

#### **INGESTION FIRST AID:**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content does not get into the lungs.

#### NOTES TO PHYSICIAN:

Aspiration may cause pulmonary edema and pneumonitis. Treat Symptomatically.

# 5. FIREFIGHTING MEASURES

#### NFPA 704 Hazard Class

Health: 1 Flammability: 1

Instability: 0



Flash Point: Flash Point Method:

150°C (300°F) COC

#### **EXTINGUISHING MEDIA:**

Carbon dioxide, water fog, foam, or dry powder. Do not use water, because this product is oil based. Water or foam may cause frothing.

## FIRE & EXPLOSION HAZARDS:

Can burn in fire, releasing toxic vapors, fumes, and smoke.

#### FIRE FIGHTING INSTRUCTIONS:

As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

## **COMBUSTION PRODUCTS:**

Hazardous decomposition products are oxides of carbon and nitrogen including CO and CO2.

# 6. ACCIDENTAL RELEASE MEASURES

#### SAFEGUARDS (PERSONNEL):

Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

#### **INITIAL CONTAINMENT:**

Absorb spills with inert material. Do not allow material to enter soil or surface water.

#### LARGE SPILLS PROCEDURE:

Absorb spill with inert material (e g, dry sand or earth), then place in a chemical waste container. Do not flush to sewer.

#### SMALL SPILLS PROCEDURE:

Absorb spills with inert material.

#### MISCELLANEOUS:

Treat or dispose of in accordance with all federal, state, and local requirements. Incineration is preferred.

# C-V 40C Cutting Oil

# **SDS - Safety Data Sheet**

# 7. HANDLING AND STORAGE

# HANDLING (PERSONNEL):

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner, or properly disposed of. Wash hands thoroughly after handling.

## HANDLING (PHYSICAL ASPECTS):

Secure container after each use. Store in a cool dry area.

Avoid contact with strong oxidizing agents.

#### STORAGE PRECAUTIONS:

Store in a cool dry place, in a tightly closed container. Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name	ACGIH	OSHA	NIOSH
Oil Mist, Mineral	TWA: 5mg/m <sup>3</sup>	TWA: 5mg/m <sup>3</sup>	TWA: 5mg/m <sup>3</sup>
	STEL: 10mg/m <sup>3</sup>	As Oil Mist, if Generated	STEL: 10mg/m <sup>3</sup>
	As Oil Mist, if Generated		As Oil Mist, if Generated

## **ENGINEERING CONTROLS:**

Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. TLV for mineral oil is 5 mg/cubic meter.

## **EYE / FACE PROTECTION REQUIREMENTS:**

When splashing of the material may occur, chemical goggles and/or a face shield are recommended.

#### SKIN PROTECTION REQUIREMENTS:

Where contact is likely, wear chemical resistant gloves.

## **RESPIRATORY PROTECTION REQUIREMENTS:**

Under normal use conditions, with adequate ventilation, no special handling equipment is required. If mists are produced, local ventilation may be required to keep exposure below limits.

## **GENERAL COMMENTS:**

Always observe good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, etc...

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Data represents typical values and are not intended to be specifications.

 FORM
 Liquid

 ODOR
 Petroleum

 VAPOR PRESSURE
 Less than 0.1 mm Hg at 68°F (20°C)

 VAPOR DENSITY
 Heavier than air (Air = 1)

 AUTOIGNITION TEMPERATURE
 Not Available

 SPECIFIC GRAVITY
 8670 Approximately

 DENSITY
 Not Determined

 VISCOSITY (approximately)
 10.0 cSt at 40 °C

 FLASH PT.
 300 °F

# C-V 40C Cutting Oil SDS - Safety Data Sheet

# 10. STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

**POLYMERIZATION:** Hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS: Avoid contact with strong oxidizing agents.

**DECOMPOSITION:** In the case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced. **CONDITIONS TO AVOID:** Excessive heat. Avoid all sources of ignition.

# 11. TOXICOLOGICAL INFORMATION

#### **GENERAL INFORMATION:**

Based on data on the components and the toxicology of similar materials

#### **ROUTES OF ENTRY:**

Skin, Eyes, Ingestion, and Inhalation.

#### ACUTE EXPOSURE:

## **EYE IRRITATION:**

Not expected to cause eye irritation. Based on data from components or similar materials. Vapors may cause irritation.

#### **SKIN IRRITATION:**

Slightly irritating based on data from components or similar materials. Prolonged or repeated skin contact without proper hygiene may result in skin disorders such as acne.

#### **RESPIRATORY IRRITATION:**

Based on data from components and similar materials, Inhalation of vapors or mists may cause irritation.

## DERMAL TOXICITY:

Expected to be of low toxicity: LD50 > 5000 mg/kg, Rabbit

#### **ORAL TOXICITY:**

Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat

#### INHALATION TOXICITY:

Based on data from components and similar materials, product is not considered to be an inhalation hazard under normal conditions of use.

## SENSITIZATION:

Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components or similar formulations.

## **CHRONIC EXPOSURE:**

#### CHRONIC TOXICITY:

No data available to indicate product or components present at greater than 1% are chronic health hazards.

## CARCINOGENICITY:

Product contains mineral and/or synthetic oils shown to be noncarcinogenic in laboratory studies with the same or similar materials. Mineral and synthetic oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.

## MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

## **REPRODUCTIVE TOXICITY**:

No data available to indicate either product or components present at greater than 0.1% that may cause reproductive toxicity.

#### TERATOGENCITY:

No data available to indicate either product or components present at greater than 0.1% that may cause birth defects.

## ADDITIONAL INFORMATION:

No other health hazards known.

# C-V 40C Cutting Oil SDS - Safety Data Sheet

# 12. ECOLOGICAL INFORMATION

# **ENVIRONMENTAL HAZARDS:**

Ecological Toxicity data has not been determined specifically for this product. The ecological toxicity hazard is based on an evaluation of data for the components or a similar material. This material is expected to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

## **ENVIRONMENTAL FATE**

This material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material. This product contains components which may be persistent in the environment.

# 13. DISPOSAL CONSIDERATIONS

# WASTE DISPOSAL:

Avoid disposal into waste water treatment facilities. Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements. This product, if discarded, is not considered a hazardous waste.

# 14. TRANSPORTATION INFORMATION

PRODUCT LABEL: ECOSE <sup>®</sup> C-V 40C Cutting Oil D.O.T SHIPPING Not Regulated by DOT.
IMDG: This material is not classified as dangerous under IMDG regulations. IATA: This material is not classified as dangerous under IATA regulations.

# 15. REGULATORY INFORMATION

## **REGULATORY LISTS SEARCHED:**

01 = CANADIAN DISCLOSURE LIST 03 = TITLE V OF THE CLEAN AIR ACT 05 = SARA TITLE III - SECTION 313 07 = CA PROPOSITION 65 No information available.

- 02 = CERCLA Hazardous Substances
- 04 = SC Toxic Air Pollutants List
- 06 = SARA Title III Section 312
- 08 = RCRA Hazardous Substances

# 16. OTHER INFORMATION

The data in this Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Nu-Tier Brands, Inc. The data on this sheet are related only to the specific material designated herein. Nu-Tier Brands, Inc. assumes no legal responsibility for use or reliance upon these data.

END OF SDS