

## Extreme Industrial EP Gear Oil

### **SDS - Safety Data Sheet**

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: ECOSE® Extreme Industrial EP Gear Oil 150

ECOSE® Extreme Industrial EP Gear Oil 220 ECOSE® Extreme Industrial EP Gear Oil 320 ECOSE® Extreme Industrial EP Gear Oil 460

Other means of identification: Industrial EP Gear Oil

SDS Number: 543150 CAS Number: Blend

CHEMTREC: 1-800-424-9300 (For emergencies)

Supplier:

Nu-Tier Brands, Inc.

8282 S. Memorial Dr., Suite 302

Tulsa, OK 74133

1-877-771-5823 (For Product Information)

www.nu-tierbrands.com

#### 2. HAZARDS IDENTIFICATION

#### **Classified Hazards**

This material is not considered hazardous by the OSHA Hazard Communication Standard 29CFR 1910.1200 GHS Precautionary Statements:

P305+351+338 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Keep out of reach of children. Read label before use.

Wash skin thoroughly after handling.

#### **Label Elements**

No classified hazards

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS	Concentration
Highly Refined Petroleum Base Oil	Mixture	85-95%
Proprietary Additives	Mixture	<15%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

#### 4. FIRST AID MEASURES

INHALATION FIRST AID: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

SKIN CONTACT FIRST AID: Wash with soap and water. Remove contaminated clothing and wash before reuse.

EYE CONTACT FIRST AID: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to

do. Continue rinsing.

INGESTION FIRST AID: Rinse mouth with water. Do NOT induce vomiting.

NOTES TO PHYSICIAN: Treat symptomatically.

#### 5. FIREFIGHTING MEASURES

NFPA 704 Hazard Class

Health: 0 Flammability: 1 Instability: 0

Flash Point Minimum: >221°C / >430°F

Flash Point Method: COC



0 (Minimal) 1 (Slight)

2 (Moderate)

3 (Serious) 4 (Severe)



# Extreme Industrial EP Gear Oil SDS - Safety Data Sheet

**Extinguishing Media**: Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F/100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

#### Specific hazards arising from the chemical:

**Unusual Fire & Explosion Hazards**: This material may burn, but will not ignite readily. If container is not properly cooled, it can rupture in the heat of a fire.

**Hazardous Combustion Products:** Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of sulfur, nitrogen or phosphorus may also be formed.

**Special protective actions for firefighters:** For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8).

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

See Section 9 for Flammable Property Including Flash Point

#### 6. ACCIDENTAL RELEASE MEASURES

Contain spilled material.

Collect in suitable and properly labeled containers.

Pick up excess with inert absorbent material.

Keep away from drains and ground water.

#### 7. HANDLING AND STORAGE

#### **HANDLING PRECAUTIONS:**

Avoid contact with eyes, skin, or clothing.

Keep away from sources of ignition.

Handle with care and avoid spillage on the floor (slippage).

#### STORAGE REQUIREMENTS:

Keep away from sources of ignition.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name	ACGIH	OSHA	Other
Oil Mist, Mineral	TWA: 5mg/m <sup>3</sup>	TWA: 5mg/m <sup>3</sup>	
	STEL: 10mg/m <sup>3</sup>	As Oil Mist, if Generated	
	As Oil Mist, if Generated		

#### **ENGINEERING CONTROLS:**

Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. TLV for mineral oil is 5 mg/cubic meter.

#### **EYE / FACE PROTECTION REQUIREMENTS:**

When splashing of the material may occur, chemical goggles and/or a face shield are recommended.

#### **SKIN PROTECTION REQUIREMENTS:**

Where contact is likely, wear chemical resistant gloves.

#### **RESPIRATORY PROTECTION REQUIREMENTS:**

Under normal use conditions, with adequate ventilation, no special handling equipment is required. If mists are produced, local ventilation may be required to keep exposure below limits.

#### **GENERAL COMMENTS:**

Always observe good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, etc...



## Extreme Industrial EP Gear Oil

### **SDS - Safety Data Sheet**

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Data represents typical values and are not intended to be specifications.

Physical State: Liquid

Odor: Mild Petroleum

Vapor Pressure: Less than 0.1mm Hg @ 68°F (20°C)

Vapor Density: Heavier than air (Air = 1)

Autoignition Temp: Not available

Specific Gravity: 0.876 – 0.895 @ 60°F (15.6°C) Approximately

Bulk Density: 7.29 – 7.46 lbs/gal Approximately

Viscosity: 150-460 cSt @40°C

Melting Point: Not determined

Flash Point: >430°F / >221°C

Test Method: COC, ASTM D92

#### 10. STABILITY AND REACTIVITY

**REACTIVITY:** Not chemically reactive.

CHEMICAL STABILITY: Stable under normal ambient and anticipated conditions of use. POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous reactions not anticipated.

CONDITIONS TO AVOID: Avoid all possible sources of ignition. Extended exposure to high temperatures can cause

decomposition.

**INCOMPATIBLE MATERIALS:** Avoid contact with strong oxidizing agents and strong reducing agents. **HAZARDOUS DECOMPOSITION PRODUCTS:** Not anticipated under normal conditions of use.

#### 11. TOXICOLOGICAL INFORMATION

#### **GENERAL INFORMATION:**

Based on data on the components and the toxicology of similar materials.

#### **ROUTES OF ENTRY:**

Skin, Eyes, Ingestion, and Inhalation.

#### **ACUTE EXPOSURE:**

#### **EYE IRRITATION:**

Not expected to cause eye irritation. Based on data from components or similar materials. Vapors may cause irritation.

#### **SKIN IRRITATION:**

Slightly irritating based on data from components or similar materials. Prolonged or repeated skin contact without proper hygiene may result in skin disorders such as acne.

#### **RESPIRATORY IRRITATION:**

Based on data from components and similar materials, Inhalation of vapors or mists may cause irritation.

#### **DERMAL TOXICITY:**

Expected to be of low toxicity: LD50 > 5000 mg/kg, Rabbit

#### **ORAL TOXICITY:**

Expected to be of low toxicity: LD50 > 5000 mg/kg, Rat

#### INHALATION TOXICITY:

Based on data from components and similar materials, product is not considered to be an inhalation hazard under normal conditions of use.

#### SENSITIZATION:

Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components or similar formulations.

#### **CHRONIC EXPOSURE:**

#### **CHRONIC TOXICITY:**

No data available to indicate product or components present at greater than 1% are chronic health hazards.



# Extreme Industrial EP Gear Oil SDS - Safety Data Sheet

#### CARCINOGENICITY:

Product contains mineral and/or synthetic oils shown to be noncarcinogenic in laboratory studies with the same or similar materials. Mineral and synthetic oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.

#### MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

#### REPRODUCTIVE TOXICITY:

No data available to indicate either product or components present at greater than 0.1% that may cause reproductive toxicity.

#### TERATOGENCITY:

No data available to indicate either product or components present at greater than 0.1% that may cause birth defects.

#### ADDITIONAL INFORMATION:

No other health hazards known.

#### 12. ECOLOGICAL INFORMATION

#### **ENVIRONMENTAL HAZARDS:**

Ecological Toxicity data has not been determined specifically for this product. The ecological toxicity hazard is based on an evaluation of data for the components or a similar material. This material is expected to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

#### **ENVIRONMENTAL FATE**

This material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material. This product contains components which may be persistent in the environment.

#### 13. DISPOSAL CONSIDERATIONS

#### **WASTE DISPOSAL:**

Avoid disposal into waste water treatment facilities. Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements. This product, if discarded, is not considered a hazardous waste.

#### 14. TRANSPORTATION INFORMATION

PRODUCT LABEL ......: ECOSE® Extreme Industrial EP Gear Oil

D.O.T SHIPPING ...... Not Regulated by DOT.

#### 15. REGULATORY INFORMATION

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA).

#### 16. OTHER INFORMATION

The data in this Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Nu-Tier Brands, Inc. The data on this sheet are related only to the specific material designated herein. Nu-Tier Brands, Inc. assumes no legal responsibility for use or reliance upon these data.

END OF SDS