

PRODUCT INFORMATION

ECOSE® GREEN CONCRETE FORM OIL

ECOSE® Green Concrete Form Oil is a ready-to-use, heavy duty compounded release agent. **ECOSE® Green Concrete Form Oil** is specially formulated with a blend of vegetable and mineral oils containing a high quality mold release agent that can be used in environmentally sensitive areas. **ECOSE® Green Concrete Form Oil** is inherently biodegradable and meets federal, local and California volatile organic compound regulations.

FEATURES AND BENEFITS:

- ✓ **Non-Staining**
- ✓ **Environmentally Friendly**
- ✓ **Reduces Voids and Bug Holes**
- ✓ **Use on Metal, Plastic and Wood Forms**
- ✓ **Ready to Use**
- ✓ **Low VOC Content**
- ✓ **Prevents Rusting of Metal Forms**
- ✓ **Prevents Buildup of Concrete On Forms**

APPLICATIONS:

ECOSE® Green Concrete Form Oil is non-staining and resists water wash-off while providing rust protection to metal forms. It is designed to impart ease of separation on wood, steel, aluminum, epoxy coated and other types of forms in both indoor and outdoor conditions. This high quality form oil may be easily applied with a roller, brush, or sprayer. Typical coverage of 500–1500 sq ft. /gal when properly applied. The applied film should be uniform and completely wet the surface. For best results, this product should be applied to a clean, dry surface.

Typical Properties

Product Code	Test Method	535710
Viscosity, cSt @ 40°C	ASTM D445	15.8
Viscosity, cSt @ 100°C	ASTM D445	3.8
Color	ASTM D1500	L1.0
Pour Point, °F (°C)	ASTM D97	-30 (-34)
Flash Point, COC, °F (°C)	ASTM D92	380 (193)
VOC content, g/L	ASTM D3960	<40
Density	ASTM D4052	7.24
Application Rate, typical	Sq./ft - gallon	500-800 (wood)
	Sq./ft - gallon	900-1500 (metal)

AVAILABILITY:

ECOSE® Green Concrete Form Oil is available throughout Nu-Tier Brands’ marketing area. Your Nu-Tier representative can provide specific information. Need additional information? Call Nu-Tier Brands @ 1-877-771-LUBE (5823) or visit www.nu-tierbrands.com.