ECOSE®

PRODUCT INFORMATION

ECOSE[®] HORIZON XHD ADVANCED HEAVY DUTY DIESEL ENGINE OIL

ECOSE[®] Horizon XHD Diesel Engine Oil provides advanced engine protection with "*next-generation*" additive technology

designed to meet modern on-highway low emission diesel engines. **ECOSE**[®] **Horizon XHD** meets or exceeds the newest **API CK-4** engine oil specification and provides outstanding wear protection necessary to satisfy the performance requirements of most North American on-highway diesel trucks. **ECOSE**[®] **Horizon XHD** Engine Oils will replace today's lubricants and will be backwards compatible with previous HD diesel engine oils.

PERFORMANCE FEATURES:

Shear Stable Formulation – maintains critical film thickness over extended use promoting extended drains
Hydro-Treated Base Oil – high purity, high VI base oils provide excellent on-highway and off-highway performance
Next-Generation Technology – improved fuel economy, engine wear protection, enhanced oxidation stability
Advanced Aeration Control - passes new Caterpillar engine oil foam testing-proven to reduce air bubbles for improved performance in severe duty off-road equipment and hydraulic valve-train actuation.

APPLICATIONS:

ECOSE® Horizon XHD can be used with complete confidence in most naturally aspirated or turbo-charged diesel engines as well as exhaust gas recirculated (EGR) engines. It provides superior performance for agricultural equipment, construction equipment, and stationary engines. It may also be used for manual transmissions and hydraulic systems where motor oil is recommended.

OEM approvals:

- Ford WSS-M2C171-F1
- Detroit Diesel 93K222

Recommended for equipment requiring:

- API Service Categories: CK-4, CJ-4, CI-4 PLUS, CI-4
- Caterpillar ECF-3, ECF-2
- Volvo VDS-4, VDS-3
- Mack EO-O, EO-M
- MTU Category 2.1 / Renault RLD-4, RLD-3
 - International (Navistar) diesel engines

Detroit Diesel (4 Stroke) 93K218

Mack EOS-4.5 / Volvo VDS 4.5

- ACEA E9, E7 / MB 228.31
- Diesel engines manufactured by OEMs not listed above, where the OEM specifies API CK-4 or CJ-4 engine oil



Product meets Cummins® Eng. Std. CES20086

Т	ypic	al F	Pro	pe	rti	es
---	------	------	-----	----	-----	----

SAE Grade		10W-30	15W-40
Product Code	Test Method	531310	531307
API Service		СК-4	СК-4
API Gravity @ 60°F	ASTM D4052	32.1	31.3
Viscosity, cSt @ 40°C	ASTM D445	81.5	114.0
Viscosity, cSt @ 100°C	ASTM D445	12.0	15.6
Viscosity Index	ASTM D2270	142	145
CCS Viscosity, cP, @ Temp.	ASTM D5293	5,850 @ -25°C	4,850 @ -20°C
Pour Point, °F	ASTM D5949	-33	-28
Flash Point, COC, °F (°C)	ASTM D92	435(224)	440 (226)
TBN	ASTM D2896	10	10
Sulfated Ash, mass %	ASTM D-874	1.0	1.0

AVAILABILITY:

11/19

ECOSE® Horizon XHD Diesel Engine Oil is available throughout Nu-Tier Brands' marketing area. Your Nu-Tier representative can provide specific information. Call Nu-Tier Brands @ 1-877-771-LUBE (5823) or visit Nu-tierbrands.com.

Nu-Tier Brands, Inc. | 8282 S. Memorial Drive, Ste 302, Tulsa, OK 74133 | (877) 771-5823 | www.nu-tierbrands.com