

PRODUCT INFORMATION

ECOSE[®] RP-6

Rust Preventative Fluid

ECOSE[®] RP-6 is a rust preventative oil formulated with an effective rust inhibitor and a high flash solvent designed for ferrous metals. Its effective rust and corrosion shield is formed by a protective coating upon evaporation of the solvent. **ECOSE RP-6** provides short term rust protection of metal parts during shipment and for temporary indoor storage under mild conditions.

FEATURES AND BENEFITS:

ECOSE[®] RP-6 offers excellent water displacing properties. Additionally, it is formulated with high quality base oil that aids in the formation of a thin film of protection that provides a coating that will not crack or peel when exposed to typical ambient temperatures.

APPLICATIONS:

ECOSE[®] RP-6 is recommended for steel surfaces in a variety of applications including machinery, tools, automotive components, marine hardware, construction equipment and any metal surface requiring a protective coating for indoor storage under mild conditions. It is applied by dipping, spraying or brushing at normal room temperatures. It is removed by petroleum solvents or conventional degreasing methods. Safety precautions should be observed in handling this product due to the solvent content.

Typical Properties

Product Code	Test Method	535380
Viscosity @ 40°C, cSt		2.0
Viscosity, SUS @ 100°F	ASTM D-445	31 - 36
Flash Point, COC, °F °C	ASTM D-92	160°F (72°C)
Color	ASTM D-1500	L1.5
Film Type		Transparent, oily
Water Displacement		PASS
Humidity Cabinet, 120°F	ASTM D-1748	+100 (hours)

***Typical test data are average values only. Minor variations which do not affect product performances are to be expected in normal manufacturing.**

AVAILABILITY:

ECOSE[®] RP-6 is available throughout Nu-Tier Brand's marketing area. Your Nu-Tier representative can provide specific information. Need additional information? Call Nu-Tier Brands @ 1-877-771-LUBE (5823) or visit Nu-tierbrands.com.