

PRODUCT INFORMATION

## ECOSE<sup>®</sup> SYNTHETIC CVT FLUID

**ECOSE<sup>®</sup> Synthetic CVT Fluid** is a new full synthetic CVT (Continuously Variable Transmission) fluid engineered and designed for use in most major brands of CVT transmissions. **ECOSE<sup>®</sup> Synthetic CVT Fluid** is formulated to meet the requirements of most American and Asian OEM manufacturers. It meets the stringent specifications and performance demands of push-belt and chain CVT's and provides outstanding performance for a wide variety of vehicles. Not recommended for Hybrid CVT units in Toyota and Ford..

### FEATURES AND BENEFITS:

- Full synthetic formulation and multi-vehicle suitability reduces inventory and costs.
- Excellent extreme pressure and anti-wear Performance for better transmission protection
- Seal compatibility for better leakage protection
- Excellent metal-on-metal friction protection
- Enhanced oxidative stability for longer fluid life and Extended service interval
- Well balanced, high level of both torque capacity and anti-shudder performance
- Ideal for service fill CVT fluid applications

### Typical Properties

Product Code	Test Method	532035
Kinematic Viscosity, cSt @ 40°C	ASTM D-445	34.5
Kinematic Viscosity, cSt @ 100°C	ASTM D-445	7.2
Viscosity Index (calculated)	ASTM D-2270	180
Brookfield Viscosity, cP @ -40°C	ASTM D-2893	8,850
Shear Stability, Visc. @ 100°C, after Sonic Shear, cSt	ASTM D-5621	6.25
Pour Point, °F (°C)	ASTM D-97	-51
Color, Visual	ASTM D-1500	<3.5

### RECOMMENDED FOR USE:

BMW / Mini Cooper EZL 799  
 Ford CVT23, CVT 30, Mercon C  
 Daihatsu Ammix CVT  
 Hyundai/Kia CVT Applications  
 Mitsubishi SP-111/CVTF-J1 & J4  
 Suzuki TC/NS-2/CVT Green 1  
 Toyota CVT TC/FE

Dodge/Jeep NS-2, CVTF +4  
 GM/Saturn (DEX-CVT)  
 Honda HMMF, HCF-2<sup>1</sup>  
 Mercedes Benz 236.20  
 Nissan, NS-1/NS-2  
 Subaru NS-2/Lineartronic CVT Fluid  
 VW/Audi TL 52180/G 052 180, G052 516

**Note:** <sup>1</sup>Not recommended for use in Honda CVT with wet-starting clutches.

### AVAILABILITY:

**ECOSE<sup>®</sup> Synthetic CVT Fluid** is available throughout Nu-Tier Brand's marketing area. Your Nu-Tier representative can provide specific information. Need additional information? Call Nu-Tier Brands @ 1-877-771-LUBE (5823) or visit [Nu-tierbrands.com](http://Nu-tierbrands.com).