



Gulf CUT AS2237-12L Cutting Oil

SDS - Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Gulf CUT AS2237-12L
Other means of identification: Metalworking Oil – Active Cutting Oil
SDS Number: 335232
CAS Number: Blend
CHEMTREC: EMERGENCY CONTACT 1-800-424-9300
Supplier:
Nu-Tier Brands, Inc., Tulsa, OK
Under License from Gulf Oil LP
TECHNICAL CONTACT NUMBER: 918-550-8026, Ext. 507
www.gulflubricants.net

2. HAZARDS IDENTIFICATION

Classified Hazards

GHS Phrases:

H315 – Causes skin irritation

H410- Very toxic to the aquatic environment – Chronic, 1

GHS Precautionary Statements:

P273 – Avoid release to the environment

P302+352 – IF ON SKIN: Wash with soap and water

Label Elements



GHS Signal Word: WARNING

GHS Classifications:

Health, Skin corrosion/irritation, 2

Environmental, Hazards to the aquatic environment, Chronic, 1

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS	Concentration
Hydrotreated petroleum oil	Various	>80%
Alkanes, Chloro, C14 – C17	61788-76-9	<5%
Non-hazardous additives	Proprietary	5-20%

4. FIRST AID MEASURES

INHALATION FIRST AID: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

SKIN CONTACT FIRST AID: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.

EYE CONTACT FIRST AID: Flush with water for several minutes. If effects occur, consult a physician.

INGESTION FIRST AID: Rinse mouth with water. If symptoms develop, obtain medical attention.



Gulf CUT AS2237-12L Cutting Oil

SDS - Safety Data Sheet

5. FIREFIGHTING MEASURES

NFPA 704 Hazard Class

Health: 1 Flammability: 1 Instability: 0



0 (Minimal)
1 (Slight)
2 (Moderate)
3 (Serious)
4 (Severe)

Flash Point: 157°C (315°F)
Flash Point Method: COC

Extinguishing Media: Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F/100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Specific hazards arising from the chemical:

Unusual Fire & Explosion Hazards: This material may burn, but will not ignite readily. If container is not properly cooled, it can rupture in the heat of a fire.

Hazardous Combustion Products: Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of sulfur, nitrogen or phosphorus may also be formed.

Special protective actions for firefighters: For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8).

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

6. ACCIDENTAL RELEASE MEASURES

SAFEGUARDS (PERSONNEL):

Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

INITIAL CONTAINMENT:

Absorb spills with inert material. Do not allow material to enter soil or surface water.

LARGE SPILLS PROCEDURE:

Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Do not flush to sewer.

SMALL SPILLS PROCEDURE:

Absorb spills with inert material.

MISCELLANEOUS:

Treat or dispose of in accordance with all federal, state, and local requirements. Incineration is preferred.

7. HANDLING AND STORAGE

HANDLING (PERSONNEL):



Gulf CUT AS2237-12L Cutting Oil

SDS - Safety Data Sheet

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner, or properly disposed of. Wash hands thoroughly after handling.

HANDLING (PHYSICAL ASPECTS):

Secure container after each use. Store in a cool dry area.
Avoid contact with strong oxidizing agents.

STORAGE PRECAUTIONS:

Store in a cool dry place, in a tightly closed container. Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

EYE / FACE PROTECTION REQUIREMENTS:

When splashing of the material may occur, chemical goggles and/or a face shield are recommended.

SKIN PROTECTION REQUIREMENTS:

Where contact is likely, wear chemical resistant gloves.

RESPIRATORY PROTECTION REQUIREMENTS:

Under normal use conditions, with adequate ventilation, no special handling equipment is required. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

GENERAL COMMENTS:

Always observe good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, etc...

9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Data represents typical values and are not intended to be specifications.

Appearance:	Light Amber	Flash Point:	318°F
Physical State:	Liquid	Density:	7.2 lb/gal approximately
Odor:	Petroleum	Solubility:	Nil in water
Viscosity:	12 cSt @ 40°F	Vapor Density:	Heavier than air (Air = 1)

10. STABILITY AND REACTIVITY

REACTIVITY: Not chemically reactive.

CHEMICAL STABILITY: Stable under normal ambient and anticipated conditions of use.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous reactions not anticipated.

CONDITIONS TO AVOID: Avoid all possible sources of ignition. Extended exposure to high temperatures can cause decomposition.

INCOMPATIBLE MATERIALS: Avoid contact with strong oxidizing agents and strong reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Not anticipated under normal conditions of use.



Gulf CUT AS2237-12L Cutting Oil

SDS - Safety Data Sheet

11. TOXICOLOGICAL INFORMATION

Repeated skin contact with this product may cause dermatitis or an oil acne.
No test data available on product.
No component is listed as a carcinogen, mutagen, or teratogen.
LD50 / LC50 - No data available

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS:

Avoid espousing to the environment, no specific aquatic data available. Ecological Toxicity data has not been determined specifically for this product. The ecological toxicity hazard is based on an evaluation of data for the components or a similar material. This material is expected to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

ENVIRONMENTAL FATE:

This material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material. This product contains components which may be persistent in the environment.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Avoid disposal into waste water treatment facilities. Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements. This product, if discarded, is not considered a hazardous waste.

14. TRANSPORTATION INFORMATION

PRODUCT LABEL: **Gulf CUT AS2237-12L**
D.O.T SHIPPING: Not Regulated by DOT.
IMDG: This material is not classified as dangerous under IMDG regulations.
IATA: This material is not classified as dangerous under IATA regulations.
TRANSPORT CANADA: This material is not classified as dangerous under Transport Canada regulations.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard:

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act (TSCA).

16. OTHER INFORMATION

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Nu-Tier Brands, Inc. The data on this sheet are related only to the specific material designated herein. Nu-Tier Brands, Inc. assumes no legal responsibility for use or reliance upon these data.

END OF MSDS

REASON FOR ISSUE: **New**
APPROVAL DATE: **October 23, 2019**
SUPERCEDES DATE: **New**
PART NUMBER ...: **335232**