



Product Bulletin

Gulf CUT NS24C

Light Colored, Low Viscosity, High Performance Cutting Oil

Gulf CUT NS24C is a light-colored, low viscosity non-staining cutting oil designed for the most demanding machining applications where high speeds and feeds are the most important aspect of the machining operation. It can be used as a machine tool lubricant and hydraulic fluid in screw machines and other automatic type machine tools.

FEATURES AND BENEFITS:

- ✓ Low foaming
- ✓ Less cutting energy required
- ✓ Permits clear view of workpiece
- ✓ High lubricity for superior finishes
- ✓ Ultra pure base oil
- ✓ Reduced tool wear
- ✓ Compatible with most materials
- ✓ Recommended for screw machines

APPLICATIONS:

Gulf CUT NS24C is versatile and can be used safely on most materials including low carbon steels, stainless steels, nickel alloys, hardened steels and aerospace aluminums: Typical applications include:

- Automatic screw machines
- Drilling
- High-speed, precision machining
- Light to medium duty machining of ductile iron
- Sawing
- Tapping and threading of mild steel
- Turning

Typical Properties

Product Code	335024
Color	Light Amber
Density, lb/gal	7.2
Viscosity cSt @ 40°C	24
Viscosity SUS @ 100°F	124
Flash point, COC	375°F
Chlorine %, wt.	Yes
Lubricity Additive	Yes
Active Sulfur %	Nil

AVAILABILITY: **Gulf CUT NS24C** is available throughout Gulf Lubricants' marketing area. Your sales representative can provide specific information. Need additional information? Call Gulf Lubricants @ 1-800-566-GULF (4853) or visit www.gulflubricants.net.

06/19

NU-TIER BRANDS, INC.

MANUFACTURER OF GULF LUBRICANTS • GULF OIL LP • TULSA, OK 74136 • Phone 918-550-8026 • Nu-Tierbrands.com