



Product Bulletin



Gulf Mineral Seal Oil

Versatile, low viscosity, colorless machining oil

Gulf Mineral Seal Oil is low viscosity, highly refined paraffin mineral oil which is almost odorless is water-white in appearance and highly oxidation stable.

FEATURES AND BENEFITS:

- Low viscosity
- Light, transparent color
- High lubricity for superior finishes
- Additive free
- Long storage life
- Recommended for screw machines

Applications:

- Cutting oil for stone and ceramics
- Diluent for cutting oil
- Light duty machining applications
- Dust mop oil
- Glass grinding oil
- Honing oil
- Lamp oil
- Gas absorption oil

Other Uses: **Gulf Mineral Seal Oil** is often used as a diluent in the manufacturing of germicides, polishes, cleaning compounds, sweeping compounds and ink oils. It may also be used as a “safety cleaning solvent” in areas where lower flash solvents would be unsafe for use

Other common uses as a base oil in the manufacturing of aluminum roll oils, drilling muds, textile oils, paper deformer, oils and caulking compounds.

Typical Properties

Product Code	335420
Color, Saybolt	30
Appearance	Clear & Bright
Gravity, °API	41.0
Density, lb/gal	6.83
Viscosity cSt @ 40°C	3.75
Aniline Point, °F	185
Flash point, COC	254°F
Copper Corrosion @ 212°F	1b
Sulfur Content, PPM	<10

**Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.*

AVAILABILITY: **Gulf Mineral Seal Oil** is available throughout Gulf Lubricants’ marketing area. Your sales representative can provide specific information. Need additional information? Call Gulf Lubricants @ 1-800-566-GULF (4853) or visit www.gulflubricants.net.

12/19

NU-TIER BRANDS, INC.

UNDER LICENSE FROM GULF OIL LP • TULSA, OK 74133 • Phone 918-550-8026 • www.gulflubricants.net or www.Nu-Tierbrands.com