



Product Bulletin

GULF NO-RUST[®] C - EP Extended Protection

Gulf No-Rust[®] C-EP is a solvent-cutback petroleum compound designed for use with both ferrous and non-ferrous metals. It forms an extended protective coating upon evaporation of the solvent. See reverse side for recommended application temperatures.

FEATURES AND BENEFITS:

Gulf No-Rust[®] C-EP has unique water displacing characteristics. Additionally, it forms a thin film of protection, providing superior metal surface protection. It provides a coating that will not crack or peel when exposed to a wide range of ambient temperatures.

APPLICATIONS:

Gulf No-Rust[®] C-EP is recommended for steel surfaces in a variety of applications including machinery, tools, automotive components, marine hardware, construction equipment and any metal surface requiring a protective coating for storage. It is applied by dipping, spraying or brushing at normal room temperatures. It is removed by petroleum solvents or conventional degreasing methods. Safety precautions should be observed in handling this product due to the solvent content.

Typical Properties

Product Code	Test Method	335381
Viscosity, cSt @ 40°C	ASTM D-445	2.5
Viscosity, SUS @ 100°F	ASTM D-2161	34
Film Type		Transparent, oily
Color		DARK
Flash Point, COC, °F °C	ASTM D-92	160°F (72°C)
Water Displacement	MIL-C-16173D	PASS
Salt Spray (5%) Hours to Failure, AVG		55
Humidity Cabinet Test, Hours Polished Panels Sandblasted Panels	ASTM D-1748	1440+ 1440+
Application Temperature, °F		40-90
Normal Protection Term, Months Indoor Outdoor, sheltered		10-12 3-4

AVAILABILITY:

Gulf No-Rust[®] C-EP is available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853) or visit Nu-tierbrands.com.

NU-TIER BRANDS, INC.

08/17

UNDER LICENSE FROM GULF OIL LP • TULSA, OK 74133 • Phone 918-550-8026 • www.gulflubricants.net or www.Nu-Tierbrands.com