



Product Bulletin

GULFCRETE GREEN CONCRETE FORM OIL

Gulfcrete Green Concrete Form Oil is a ready-to-use, heavy duty compounded release agent. **Gulfcrete Green** is specially formulated with a blend of vegetable and mineral oils containing a high quality mold release agent that can be used in environmentally sensitive areas. **Gulfcrete Green** is inherently biodegradable and meets federal, local and California volatile organic compound regulations.

New York State DOT Approved Concrete Form Coating, Section 555 – Structural Concrete.

FEATURES AND BENEFITS:

- ✓ **Non-Staining**
- ✓ **Environmentally Friendly**
- ✓ **Reduces Voids and Bug Holes**
- ✓ **Use on Metal, Plastic and Wood Forms**
- ✓ **Ready to Use**
- ✓ **Low VOC Content**
- ✓ **Prevents Rusting of Metal Forms**
- ✓ **Prevents Buildup of Concrete On Forms**

APPLICATIONS:

Gulfcrete Green is non-staining and resists water wash-off while providing rust protection to metal forms. It is designed to impart ease of separation on wood, steel, aluminum, epoxy coated and other types of forms in both indoor and outdoor conditions. This high quality form oil may be easily applied with a roller, brush, or sprayer. Typical coverage of 500–1500 sq ft. /gal when properly applied. The applied film should be uniform and completely wet the surface. For best results, this product should be applied to a clean, dry surface.

Typical Properties

| Product Code | Test Method | 335710 |
|----------------------------------|-----------------|--------------------|
| Viscosity, cSt @ 40°C | ASTM D445 | 15.8 |
| Viscosity, cSt @ 100°C | ASTM D445 | 3.8 |
| Color | ASTM D1500 | L1.0 |
| Pour Point, °F (°C) | ASTM D97 | -30 (-34) |
| Flash Point, COC, °F (°C) | ASTM D92 | 380 (193) |
| VOC content, g/L | ASTM D3960 | <40 |
| Density | ASTM D4052 | 7.24 |
| Application Rate, typical | Sq./ft - gallon | 500 - 800 (wood) |
| | Sq./ft - gallon | 900 - 1500 (metal) |

AVAILABILITY:

Gulfcrete Green Concrete Form Oil is available throughout Gulf Lubricants' marketing area. Your sales representative can provide specific information. Need additional information? Call Gulf Lubricants@ 1-800-566-Gulf (4853) or visit www.Gulflubricants.net.