



Gulfpride® High Performance Motor Oil

SDS - Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Gulfpride® High Performance Motor Oil, 5W-20
 Gulfpride® High Performance Motor Oil, 5W-30

Other means of identification: Motor Oil, Synthetic Blend

SDS Number: 330120

CAS Number: Blend

CHEMTREC: EMERGENCY CONTACT 1-800-424-9300

Supplier:
 Nu-Tier Brands, Inc., Tulsa, OK
 Under License from Gulf Oil LP
 TECHNICAL CONTACT NUMBER: 918-550-8026, Ext. 507
 www.gulf lubricants.net

2. HAZARDS IDENTIFICATION

Classified Hazards	Other Hazards
This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.	None Known

Label Elements

No classified hazards

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture: Mixture

Other means of identification: Motor oil

CAS number/other identifiers:

CAS number: Not applicable

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

4. FIRST AID MEASURES

INHALATION FIRST AID: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

SKIN CONTACT FIRST AID: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.

EYE CONTACT FIRST AID: Flush with water for several minutes. If effects occur, consult a physician.

INGESTION FIRST AID: Rinse mouth with water. If symptoms develop, obtain medical attention.

5. FIREFIGHTING MEASURES

NFPA 704 Hazard Class

Health: 1 Flammability: 1 Instability: 0



0 (Minimal)
 1 (Slight)
 2 (Moderate)
 3 (Serious)
 4 (Severe)

Flash Point Minimum: 400°F (204°C)
Flash Point Test Method: Cleveland Open Cup (COC)



Gulfpride[®] High Performance Motor Oil

SDS - Safety Data Sheet

Extinguishing Media: Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F/100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Specific hazards arising from the chemical:

Unusual Fire & Explosion Hazards: This material may burn, but will not ignite readily. If container is not properly cooled, it can rupture in the heat of a fire.

Hazardous Combustion Products: Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of sulfur, nitrogen or phosphorus may also be formed.

Special protective actions for firefighters: For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant. Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

Methods and Materials for Containment and Clean Up:

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal. There may be specific federal regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see Section 15: Regulatory Information.

7. HANDLING AND STORAGE

Precautions for Safe Handling:

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. These products have a low vapor pressure and are not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes.

Conditions for Safe Storage, Including Any Incompatibilities:

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Store locked up. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

Incompatibilities:

Oxidizing materials, acids, reactive halogens.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits:

ACGIH, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

Appropriate Engineering Controls:

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.



Gulfpride[®] High Performance Motor Oil

SDS - Safety Data Sheet

Individual Protective Measures, such as Personal Protective Equipment:

Protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: safety glasses, gloves, lab coat, or apron.

Eyes/Face Protection:

Safety glasses with side shields should be worn at a minimum. Additional protection, such as goggles, face shields, or respirators may be needed depending upon anticipated use and concentrations of mists or vapors. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. Contact lens use is not recommended.

Skin Protection:

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber or equivalent gloves is not recommended.

Respiratory Protection:

No respirator is required under normal conditions of use. Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Consult with a health and safety professional for specific respirators appropriate for your use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Data represents typical values and are not intended to be specifications.

Appearance:	Amber	Flash Point Minimum:	400°F / 204°C
Physical State:	Liquid	Test Method:	Cleveland Open Cup, ASTM D92
Odor:	Petroleum	Initial Boiling Point/Range:	475°F (246°C) (minimum)
Odor Threshold:	No data	Vapor Pressure:	<1 mm Hg @ 68°F (20°C)
pH:	Not applicable	Partition Coefficient (n-octanol/water) (Kow):	No data
Viscosity:	>30 mm ² /s @ 104°F (40°C)	Melting/Freezing Point:	No data
Upper Explosive Limits:	No data (vol % in air)	Auto-ignition Temperature:	No data
Lower Explosive Limits:	No data (vol % in air)	Specific Gravity:	0.85 @ 68°F (20°C) (water=1)
Evaporation Rate:	No data (nBuAc=1)	Bulk Density:	7.12 lbs/gal (880 g/l)
Solubility (Water):	Insoluble		

10. STABILITY AND REACTIVITY

REACTIVITY: Not chemically reactive.

CHEMICAL STABILITY: Stable under normal ambient and anticipated conditions of use.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous reactions not anticipated.

CONDITIONS TO AVOID: Avoid all possible sources of ignition. Extended exposure to high temperatures can cause decomposition.

INCOMPATIBLE MATERIALS: Avoid contact with strong oxidizing agents and strong reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Not anticipated under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Toxicity Data and Information:

Component Analysis - LD50/LC50

Petroleum distillates, solvent-refined heavy paraffinic (64741-88-4)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg

Residual oils (petroleum), solvent refined (64742-01-4)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg



Gulfpride[®] High Performance Motor Oil

SDS - Safety Data Sheet

Residual oils (petroleum), solvent dewaxed (64742-62-7)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg

Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

Oral LD50 Rat >5000 mg/kg

Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (72623-87-1)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg

Information on Likely Routes of Exposure

Inhalation

No information on significant adverse effects.

Ingestion

May be harmful if swallowed.

Skin Contact

No information on significant adverse effects.

Eye Contact

No information on significant adverse effects.

Immediate Effects

No information on significant adverse effects.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity

May cause slight skin and respiratory irritation.

Respiratory Sensitization

No information available for the products.

Skin Sensitization

No information available for the product.

Carcinogenicity

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

Germ Cell Mutagenicity

No information available for the product.

Teratogenicity

No information available for the product.

Reproductive Effects

No epidemiological data is available for the product.

Specific Target Organ Effects - Single Exposure

No information on significant adverse effects.

Specific Target Organ Effects - Repeated Exposure

No information on significant adverse effects.

Aspiration Hazard

No data available.

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.



Gulfpride[®] High Performance Motor Oil

SDS - Safety Data Sheet

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life.

Component Analysis - Ecotoxicity - Aquatic Toxicity

Petroleum distillates, solvent-refined heavy	Concentration/Conditions
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L
48 Hr EC50 Daphnia magna	>1000 mg/L
Residual oils (petroleum), solvent refined (64742-01-4)	Concentration/Conditions
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L
48 Hr EC50 Daphnia magna	>1000 mg/L

Residual oils (petroleum), solvent dewaxed (64742-62-7)

Duration/Test/Species	Concentration/Conditions
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L
48 Hr EC50 Daphnia magna	>1000 mg/L

Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

Duration/Test/Species	Concentration/Conditions
96 Hr LC50 Lepomis macrochirus	>10000 mg/L

Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (72623-87-1)

Duration/Test/Species	Concentration/Conditions
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L
48 Hr EC50 Daphnia magna	>1000 mg/L

Petroleum distillates, hydrotreated heavy naphthenic (64742-52-5)

Duration/Test/Species	Concentration/Conditions
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L
48 Hr EC50 Daphnia magna	>1000 mg/L

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

Duration/Test/Species	Concentration/Conditions
96 Hr LC50 Pimephales promelas	1.0 - 5.0 mg/L [static]
96 Hr LC50 Pimephales promelas	10.0 - 35.0 mg/L [semi-static]
48 Hr EC50 Daphnia magna	1 - 1.5 mg/L

Persistence and Degradability

No information available for the product.

Bioaccumulation Potential

No information available for the product.

Mobility in Soil

No information available for the product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS:

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste.

These products, if discarded, are not expected to be a characteristic or listed hazardous waste. If recycled as used oil in the USA, they can be managed in accordance with the used oil exemption under 40 CFR Part 279. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of these products.



Gulfpride[®] High Performance Motor Oil

SDS - Safety Data Sheet

14. TRANSPORTATION INFORMATION

Emergency Response Guide Number: Not applicable.
DOT Shipping Name: Not regulated as a hazardous material.
TDG Shipping Name: Not regulated as a dangerous good.

15. REGULATORY INFORMATION

Volatile Organic Compounds (As Regulated):

Negligible as per U.S EPA 40 CFR 51.100(s)

Federal Regulations

SARA 302/304

Component Analysis:

Based on the ingredient(s) listed in SECTION 3, this product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

SARA 311/312 Hazardous Categories:

Acute Health: No **Chronic Health:** No **Fire:** No **Pressure:** No **Reactive:** No

SARA Section 313

Component Analysis:

This product does not contain any "toxic" chemical subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

CERCLA

Component Analysis

Based on the ingredient(s) listed in SECTION 3, this product does not contain any "hazardous substance" listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

TSCA Inventory

All the components of these products are listed on, or are automatically included as "naturally occurring chemical substances" on, or are exempted from the requirement to be listed on, the TSCA Inventory.

U.S. State Regulations

None of this product's components are listed on the state lists from CA, MA, MN, NJ or PA.

No component(s) are listed under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).

Canadian Regulations

These products have been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

16. OTHER INFORMATION

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Nu-Tier Brands, Inc. The data on this sheet are related only to the specific material designated herein. Nu-Tier Brands, Inc. assumes no legal responsibility for use or reliance upon these data.

END OF MSDS