



# Product Bulletin



## GULF FORM OIL

### *Ready Separation of Forms from Concrete*

**Gulf Form Oil** is a ready-to-use, non-staining concrete releasing agent that can be used on metal and wooden forms. It is formulated with light viscosity mineral oil and a unique additive system to prevent cement from adhering to form surfaces. **Gulf Form Oil** resists water wash-off while providing rust protection to metal forms. This product meets federal guidelines for VOC compliance and can be applied using a brush, spray or roller application.

#### FEATURES AND BENEFITS:

- ✓ Non Staining
- ✓ Ready to Use
- ✓ Prevents Concrete Build Up on Forms
- ✓ Use on Metal, Plastic and Wood Forms
- ✓ Good Low Temperature Use
- ✓ Low VOC Content
- ✓ Prevents Rusting of Metal Forms
- ✓ Prevents Buildup of Concrete on Forms

#### APPLICATIONS:

**Gulf Form Oil** is designed to impart easy of separation on wood, steel, aluminum, epoxy coated and other types of forms in both indoor and outdoor conditions. It may be easily applied with a roller, brush, or sprayer. The applied film should be uniform and completely wet the surface. For best results, this product should be applied to a clean, dry surface.

#### Typical Properties

Product Code	Test Method	335712
Viscosity, cSt @ 40°C	ASTM D445	17.5
Viscosity, cSt @ 100°C	ASTM D445	3.85
Viscosity Index	ASTM 2270	111
Pour Point, C° (F°)	ASTM 5946	-23 (-10°F)
Color	ASTM D1500	L1.0
Wetting Agent	Report	Present
Flash Point, COC, °F (°C)	ASTM D92	378 (192)
VOC content, U.S. EPA & State Requirements (g/l)	ASTM D3960	Meets (<30)
Density	ASTM D4052	7.11

*Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.*

#### AVAILABILITY:

**Gulf Form Oil** is available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF(4853) or visit [www.GulfLubricants.net](http://www.GulfLubricants.net).