



Product Bulletin



GULFPRIDE[®] HIGH MILEAGE MOTOR OIL

HELPS TO REMOVE ENGINE SLUDGE and REDUCE WEAR

Gulfpride[®] High Mileage Motor Oil is uniquely formulated for gasoline engine powered vehicles with 75,000 miles or more. This oil has proven to reduce high temperature varnish deposits and ring sticking and is an excellent choice for use in all seasons. All viscosity grades meet the latest requirements of **API SP** and **ILSAC GF-6A** performance as well as meeting the requirements of all previous API "S" categories including SN Plus, SN, and SM.

Gulfpride[®] High Mileage Motor Oil helps to condition seals and makes them less susceptible to leaking. Its synthetic blend formulation offers excellent low-temperature pumpability for protection during cold start-ups. **Gulfpride[®] High Mileage Motor Oil** is also recommended for use in lower mileage vehicles, including new cars still under warranty.

Typical Properties

SAE Grade		5W-20	5W-30	10W-30
Product Code	Test Method	330502	330503	330513
Gravity, API	ASTM D-4052	32.8	33.0	31.9
Kinematic Viscosity, cSt at 40°C	ASTM D-445	50.0	62.7	71.4
Kinematic Viscosity, cSt at 100°C	ASTM D-445	8.6	10.5	10.8
Viscosity Index, calculated		151	158	141
Pour Point °F	ASTM D-97	-43	-43	-33
Cold Cranking at temp °C, cP	ASTM D-5293	5500 @ -30	5300 @ -30	5800 @ -25
Color	ASTM D-1500	L3.0	L3.5	L3.5
Flash Point (COC) °F	ASTM D-92	430	430	450
Zinc, % wt PPM		850	850	850
Highest API Performance		SP	SP	SP
Highest ILSAC Performance		GF-6A	GF-6A	GF-6A

**Note: Values shown are typical only and do not constitute a specification. Minor variations in product are to be expected in normal manufacturing. Always confirm with the original manufacturer's recommendation for proper equipment operating requirements.*

AVAILABILITY:

Gulfpride[®] High Mileage Motor Oil is available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853) or visit Nu-Tierbrands.com.