



LUBRICANTS



Product Data Sheet

Gulfpride® Synthetic Multi-Vehicle DEXRON® VI ATF

OEM Approved, Low Viscosity Automatic Transmission Fluid

Engineered to surpass the performance requirements of GM, Ford and Toyota where the manufacturer requires a low-viscosity, fuel efficient automatic transmission fluid (ATF). It is licensed and approved for use in General Motors automatic transmissions requiring DEXRON® VI, the only GM approved specification for vehicles of model years 2006 and newer.

Features and Benefits

- Full Synthetic, low viscosity formulation
- Anti-foam agents designed to improve hydraulic function
- Superior anti-wear protection and highly shear stable synthetic components
- Excellent sludge and varnish resistance promote clean trouble-free performance
- Improved friction properties provide smooth shifting throughout service life of transmission

Approvals

- License Number J-60183 General Motors specification GMN 10060

Applications

- DEXRON® VI
- MERCON® LV
- Toyota WS
- Honda Z-1, Honda DW-1, Nissan Matic J, Matic S and Hyundai SP-IV
- Anywhere DEXRON-II and DEXRON-III fluids in older GM automatic transmissions are specified

Typical Properties

Product Code	Test Method	330030
Kinematic Viscosity, cSt @ 40°C	ASTM D-445	28.5
Kinematic Viscosity, cSt @ 100°C	ASTM D-445	5.85
Viscosity Index (calculated)	ASTM D-2270	157
Brookfield Viscosity, cP @ -40°C	ASTM D-2893	8,500
Pour Point, °F	ASTM D-97	-54
Color, Visual		Red

Note: Typical values shown are representative of current production and may vary within modest range.



918-550-8026



Tulsa, OK 74133



www.nu-tierbrands.com



Suitable For Use Applications:

- Acura ATF-Z1
- Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1
- Allison C-3 & C-4
- American Motors ATF +3 (MS7176-E), ATF +4 (MS9602)
- ATF RED 1, RED 1K
- Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)
- Audi/VW 052 055
- Audi/VW G 052 025-A2
- Audi/VW G 052 162 (ZF Lifeguardfluid 5) (ZF No. S671 090 170)
- Audi/VW G 052 162-A1/A2
- Audi/VW G 052 990
- Audi/VW G 053 025-A2
- Audi/VW G 055 025 A2 (JWS 3309)
- Audi/VW G 055 162-A2, -A6 (ZF Lifeguardfluid 6 Plus) (ZF No. S671 090 281)
- Audi/VW G 055 540 (A2)
- Audi/VW G 060 162 (ZF Lifeguardfluid 8) (ZF No. S671 090 312)
- Bentley PY112995PA
- BMW 704SE
- BMW ETL 8072B
- BMW JWS 3309 (T-IV)
- BMW LA2634
- BMW LT71141 (ZF 5 HP 18FL/19FL/24A)
- BMW MINI
- BMW ZF 5HP18FL, 5HP24, 5HP30
- Bosch TE-ML 09
- CAT T0-2
- Chrysler ATF+, +2, +3 (MS 7176E), +4 (MS 9602)
- Chrysler/Dodge MOPAR AS 68 RC and AS 69 RC (T-IV), JWS 3309
- Chrysler/Dodge/Jeep 05127382AA
- Chrysler/Dodge/Jeep 68043742AA
- Chrysler/Dodge/Jeep 68171866AA
- Daewoo LT 71141
- Daihatsu AMMIX ATF D-II
- Daihatsu AMMIX ATF D-III SP
- Esso LT 71141
- FIAT T-IV type, JWS 3309
- Ford ESP-M2C166H, XL-12
- Ford FNRS (Mazda M5, XT-9-QMM5)
- Ford MERCON®
- Ford MERCON® LV (FF-WSS-M2C-93BA/SF, XT-10 QLV)
- Ford WSS M2C 138C1, 166H
- Ford WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309
- Ford/Lincoln/Mercury XT-2-QDX (M)
- Ford/Lincoln/Mercury XT-2-QSM (Syn)
- Fuso ATF-A4
- Fuso ATF-II
- Fuso ATF-SPIII
- GM 1940700
- GM 1940767
- GM 21005966
- GM 22717466
- GM 88900925
- GM 93160393
- GM 9986195
- GM DEXRON®-II
- GM DEXRON®-IID
- GM DEXRON®-IIE
- GM DEXRON®-IIIG
- GM DEXRON®-IIII
- GM DEXRON®-VI
- GM TASA
- GM/GMC/Opel/Saturn 88863400
- GM/GMC/Opel/Saturn 88863401
- GM/GMC/Opel/Saturn AW1
- GM/GMC/Opel/Saturn V1
- GM9986195 (Aisin AW, JWS 3309)
- Hino Blue ribbon ATF
- Honda ATF Ultra II
- Honda ATF-Z1 (except in CVTs)
- Honda DW-1
- Honda Type 2.0
- Honda Type 3.0 / 3.1
- Hyundai/Kia 040000C905G
- Hyundai/Kia Dex-II/ SP-II
- Hyundai/Kia JWS 3314
- Hyundai/Kia NUMM040 CH20 Red-1
- Hyundai/Kia NWS 9638
- Hyundai/Kia SPH-IV
- Hyundai/Kia SP-III
- Hyundai/Kia SP-IV (00232-1904/04500-00115)
- Hyundai/Kia SP-IV M (SP4-M)
- Hyundai/Kia SP-IV-RR
- Idemitsu K17 3100 PL085
- ISUZU 08200-9001
- ISUZU BESCO ATF SP
- ISUZU BESCO ATF-II
- ISUZU BESCO ATF-III
- ISUZU SCS Fluid
- Jaguar 02JDE26444
- Jaguar ATF 3403 JLM20238,
- Jaguar ATF 3403 M115, ATF 3403-M115,
- Jaguar ATF LT71141, ZF 5HP24
- Jaguar Fluid 8432
- Jaguar JLM 20292
- Jaguar JLM20238
- Jaguar K17
- JASO M315-2013 1A
- JASO M315-2013 1A-LV
- JASO M315-2013 2A
- JEEP ATF+3, +4
- KIA ATF SP-II, SP-III, SP-IV, SP-IVM, Red 1
- Land Rover LR023288
- Lexus JWS 3309
- MAN 339A
- MAZDA ATF 3317
- Mazda ATF D-II
- Mazda ATF F-1
- Mazda ATF FZ
- Mazda ATF M-III
- Mazda ATF M-V
- Mazda ATF N-1
- Mazda ATF S-1
- MB ZF 4HP20
- MINI COOPER T-IV
- Mitsubishi Diaqueen ATF PA
- Mitsubishi Diaqueen AW
- Mitsubishi Diaqueen J2
- Mitsubishi Diaqueen J3
- Mitsubishi Diaqueen SK
- Mitsubishi Diaqueen SP-II
- Mitsubishi Diaqueen SP-III
- Mitsubishi Diaqueen SP-IV
- NAG 1 (Chrysler, Jeep, Cherokee)
- Nissan Matc Fluid C
- Nissan Matc Fluid D
- Nissan Matc Fluid J
- Nissan Matc Fluid K
- Nissan Matc Fluid S
- Opel/GM 19 40 700
- Opel/GM 19 40 767
- Opel/GM 21005966 Transaxle
- Opel/GM 22 17466
- Opel/GM 88900925
- Opel/GM 9986195
- Peugeot ZF 4HP20
- Peugeot/Citreon (PSA) AL4 Automatic gearbox oil (#9730AE)
- Peugeot/Citreon Z 000169756
- Porsche 000 043 205 09
- Porsche 000 043 205 28
- Porsche 999 917 547 00 (A2)
- Porsche ATF 3403-M115,
- Porsche T-IV (JWS 3309)
- Porsche Z 000169756
- Porsche ZF 5HP19FL, ZF 5HP20, LT71141
- Porsche ZF 5HP20
- Porsche LT71141
- Renault DPO/ALA
- Renault Matc D2
- Renault Samsung SATF-D
- Saab 93 160 393
- Saab 93 165 147
- Saab T-IV (JWS 3309)
- Saturn T-IV (JWS 3309)
- Scion (all vehicles)
- Shell 3403, M115, LA 2634
- Shell L 12108
- Ssang yong DSIH 5M-66
- Subaru ATF
- Subaru ATF 5AT
- Subaru ATF, ATF HP
- Subaru DEXRON®-II
- Subaru K0140Y0700
- Suzuki AT OIL 5D06
- Suzuki ATF 2326
- Suzuki ATF 2384K
- Suzuki ATF 3314
- Suzuki ATF 3317
- Suzuki ATF AW-1
- Suzuki JWS 3309
- Texaco 7045-E
- Texaco 8072B
- Texaco N402
- Toyota ATF D-II
- Toyota ATF D-III
- Toyota ATF T-III
- Toyota ATF T-IV
- Toyota ATF WS
- Vickers M2950-S, i-286-S
- Voith 55.6335.xx (G607)
- Voith Svc Bltn #013 and #118
- Volvo 97325
- Volvo 97335
- Volvo CE 97340
- Volvo PN 1161521
- Volvo PN 1161540/1161640
- Volvo PN 1161621
- Volvo PN 31256774/31256675
- VW 5 HP (ZF 5 HP 30)
- VW 5HP (18FL, 30)
- VW 5HP (19FL, 24A)
- VW G 052 162 (ZF Lifeguardfluid 5)
- VW G 055 162-A2, -A6 (ZF Lifeguardfluid 6 Plus)
- VW G 060 162 (ZF Lifeguardfluid 8)
- VW G US 000 162
- VW G055 540 (A2)
- VW G-055-025 A2 (JWS 3309)
- VW TL 521 62
- ZF 8 speed transmissions
- ZF 9 speed transmissions
- ZF 10 speed transmissions
- ZF all 3 & 4 speed transmission
- ZF TE-ML 05L
- ZF TE-ML 09
- ZF TE-ML 11A, 11B, ZF TE-ML 21L



1-800-566-4853



Tulsa, OK 74133



www.nu-tierbrands.com



Note: Always consult vehicle owner's manual and/or dipstick for proper fluid type and recommended drain interval.

1. **Gulfpride® Synthetic Multi-Vehicle DEXRON® VI ATF is backward compatible and replaces DEXRON® III fluids in older GM automatic transmissions. (DEXRON® VI specification supersedes the obsolete DEXRON® III in GM vehicles.)
Note: Not for use with Ford Type F applications or any DCT (Dual Clutch Transmission) or CVT (Continuously Variable Transmission).**
2. **Some of these specifications are for high viscosity applications. Gulf Synthetic Multi-Vehicle DEXRON® VI can be used in these applications outside of warranty without causing harm to the transmission; however, the viscosity profile may not meet the specification requirements and may be subject to regulation in some countries and states in the U.S. such as California.**
3. **If you need additional assistance with identification of which specifications you should claim, please contact your Gulf Lubricants sales representative for more information.**
4. **In the event a part number or application listed above is specified for a CVT or a DCT, do not use this fluid.**
The exclusion of CVT and DCT transmissions supersedes the specific listing above.
5. ***JASO M315-2013 1A, JASO M315-2013 2A- Suitable for Use- Does Not Meet the High Viscosity Requirements.**

Rev. 5/21



1-800-566-4853



Tulsa, OK 74133



www.nu-tierbrands.com

