



LUBRICANTS



Product Data Sheet

GULFPRIDE® HIGH MILEAGE MOTOR OIL

HELPS TO REMOVE ENGINE SLUDGE and REDUCE WEAR

Uniquely formulated for gasoline engine powered vehicles with 75,000 miles or more. This oil has proven to reduce high temperature varnish deposits, ring sticking and is an excellent choice for use in all seasons.

Features and Benefits

- Provides extra wear protection
- Excellent low-temperature pumpability
- Provides extra cleaning to critical engine parts
- Condition seals and makes them less susceptible to leaking

Approvals

- API SP / ILSAC GF-6A
- Previous API "S" categories including SN Plus, SN, and SM

Applications

- Lower mileage vehicles, including new cars still under warranty
- Older mileage and rebuilt passenger cars, light duty trucks and SUVs

Typical Properties

SAE Grade	Test Method	5W-20	5W-30	10W-30
Product Code		330502	330503	330513
Gravity, API	ASTM D-4052	32.8	33.0	31.9
Kinematic Viscosity, cSt at 40°C	ASTM D-445	50.0	62.7	71.4
Kinematic Viscosity, cSt at 100°C	ASTM D-445	8.6	10.5	10.8
Viscosity Index, calculated		151	158	141
Pour Point °F	ASTM D-97	-43	-43	-33
Cold Cranking at temp °C, cP	ASTM D-5293	5500 @ -30	5300 @ -30	5800 @ -25
Color	ASTM D-1500	L3.0	L3.5	L3.5
Flash Point (COC) °F	ASTM D-92	430	430	450
Zinc, % wt PPM		850	850	850

Note: Values shown are typical only and do not constitute a specification. Minor variations in product are to be expected in normal manufacturing. Always confirm with the original manufacturer's recommendation for proper equipment operating requirements

Rev. 05/21



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

