



LUBRICANTS

Product Data Sheet

Gulf Super Duty Select XFE

Synthetic Blend, Severe Duty, Fuel Efficient

New-generation diesel engine oil specifically formulated for API FA-4 compliant engines operating under extreme conditions. It is engineered to help extend engine life and provide longer oil drain capability. Provides additional fuel economy compared to API CK-4 or API CJ-4 SAE 10W-30 engine oils.

Features and Benefits

- Excellent cold weather starts with low temperature fluidity and pumpability
- Improved fuel economy in engines designed to operate with lower viscosity oils
- Maintain its viscosity under high-temperature/high-shear conditions
- Excellent wear protection and outstanding TBN retention.

Approvals

- API Service FA-4

Applications

- For use in API FA-4 compliant engines
- Meets performance outlined by Cummins CES 20087 and Detroit Fluid Specification 93K223

Typical Properties

Product Code - 331336	Test Method	SAE 10W-30
API Service		FA-4
Kinematic Viscosity, cSt @40°C	ASTM D 445	64.0
Kinematic Viscosity, cSt @100°C	ASTM D 445	10.5
Viscosity Index	ASTM D 2270	153
CCS @ -25°C, cP	ASTM D 5293	5,300
Pour Point, °C	ASTM D 5949	-36
Color	ASTM D 1500	L3.5
Sulfated Ash, wt%	ASTM D 92	1.0
Total Base Number, mg KOH/g	ASTM D 2896	10.0
HTHS @ 150°C, cP	ASTM D 4683	3.1

NOTE: Gulf Super Duty Select XFE 10W-30 engine oil should only be used where an API FA-4 oil is recommended by the OEM. Before using this product in an engine, users should consult recommendations as outlined in the owner's manual or other service bulletins.

REV. 05/21



918-550-8026



Tulsa, OK 74133



www.nu-tierbrands.com

