



LUBRICANTS



# Product Data Sheet

## Transcrest® Tractor Hydraulic Fluid

### *Multifunctional JD J20C Tractor Fluid*

Premium transmission/differential/hydraulic fluid formulated from high-quality base oil and a performance proven additive system. It is designed to function as a common sump fluid in a wide variety of farm tractors and construction equipment requiring a single lubricant for the hydraulic system, powershift/hydrostatic/manual transmissions final drive, wet brakes, and power-take-off (PTO) clutches. It is suited for year-round use as a universal lubricant for today's modern tractors, as well as yesterday's workhorses. Provides outstanding wear protection for gears and hydraulic pumps and meets API GL-4 performance requirements.

### Features and Benefits

- Meets API GL-4 gear oil performance
- Maintains viscosity under severe service conditions
- Friction modifiers for superior wet brake chatter control
- Outstanding wear protection for gears and hydraulic systems

### Applications

- AGCO Power Fluid 821XL
- Allison C-4
- API GL-4
- CAT TO-2
- Yanmar
- CNH MAT 3525, 3526, 3505, 3510, 3540
- Denison HF-0, HF-1, HF-2
- Sperry Vickers / Eaton I-286-S, M2950S
- Ford M2C134-D, M2C86B, C
- FNHA 2C 201
- John Deere J20C, J20D
- Kubota UDT, Super UDT2
- Massey Ferguson M-1135, M-1143, M-1145
- International Harvester Hy-Tran B-6
- White Q-1826
- Sauer Sunstrand/Danfoss: Hydrostatic Trans Fluid

### Suitable for Use In

- Komatsu
- Case IH
- David Brown
- Ford New Holland
- Volvo
- White and others
- AGCO Kubota
- Mahindra
- Massey Ferguson
- John Deere
- KH Deutz



1-800-566-4853



Tulsa, OK 74133



[www.nu-tierbrands.com](http://www.nu-tierbrands.com)





LUBRICANTS



# Product Data Sheet

## Typical Properties

SAE Grade	Test Method	10W-30
Product Code		331953
Viscosity, cSt @ 40°C	ASTM D-445	57.5
Viscosity, cSt @ 100°C	ASTM D-445	9.3
Brookfield Viscosity, cP @ -35°C	ASTM D-2983	18,500
Viscosity Index	ASTM D-2270	145
Pour Point, °F	ASTM D-5949	-35
Flash Point, COC, °F	ASTM D-92	400
Gravity, API	ASTM D-4052	30.5

Note: Refer to equipment owner's manual for proper lubricant recommendation

Rev. 05/21



1-800-566-4853



Tulsa, OK 74133



[www.nu-tierbrands.com](http://www.nu-tierbrands.com)

