

## **Transcrest<sup>®</sup> Low Temperature Tractor Fluid**

### Premium Low Temperature JD J20D Tractor Hydraulic Fluid

Multifunctional tractor/hydraulic fluid designed to lubricate transmissions, differentials and final drive gears at very low temperatures in most farm tractors and equipment that utilize a common fluid reservoir. **Transcrest® Low Temperature Tractor Fluid** is specifically designed to meet the *John Deere J20D* specification which provides for outstanding low temperature fluidity under the coldest of conditions while eliminating wet brake and PTO "chatter". Provides outstanding protection from corrosion and rust, while offering excellent water tolerance and good filterability characteristic.

#### **Features and Benefits**

- Specially designed for low temperature performance
- Smooth, quiet hydraulic pump action
- Excellent gear wear protection
- Enhanced wet brake and PTO chatter control
- Advanced rust and corrosion protection for vital internal parts
- Provides excellent shifting action under extreme cold temperature conditions

#### **Applications**

- John Deere J20D, low viscosity for cold climates
- John Deere J20C\*
- Ford M2C134-D\*
- Kubota UDT\*
- White Farm Q-1826\*
- Caterpillar TO-2

- Denison HF-0, HF-1, HF-2
- Sperry Vickers I-286-S
- Sperry Vickers M-2950-S
- Sundstrand Hydraulics
- Plessey-Sundstrand

\*Intended for low temperature applications as recommended by these OEM's









# **Product Data Sheet**

#### **Typical Properties**

SAE Grade	Test Method	5W-20
Product Code		331955
Gravity, °API	ASTM D-4052	32
Flash Point, COC, °F	ASTM D-92	425
Flash Point, COC, °C	ASTM D-92	218
Pour Point, °F	ASTM D-5949	-40
Pour Point, °C	ASTM D-5949	-40
Viscosity @ 40° cSt	ASTM D-445	38.5
Viscosity @ 100° cSt	ASTM D-445	7.5
Viscosity Index (min)	ASTM D-2270	166
Copper Corrosion Test	ASTM D-130	Pass
Foam Test	ASTM D-892	Pass
Sulfated Ash, % wt.	ASTM D-874	2.0 max.
Color	ASTM D-1500	5 max.

Note: Refer to equipment owner's manual for proper lubricant recommendation

Rev. 05/21



9



