



LUBRICANTS



# Product Data Sheet

## Gulf SS Tractor Fluid

### *Premium Shear Stable (SS) Tractor Hydraulic Fluid*

Highly shear stable, premium multi-purpose tractor fluid formulated to exceed original equipment manufacturers (OEM) performance requirements. Uniquely formulated with an advanced additive package, this fluid offers exceptional resistance to viscosity loss due to shearing over conventional tractor fluids. This fluid is designed to function as a common sump fluid in a wide variety of agricultural, mining and construction equipment that requires one fluid be used to lubricate the hydraulic system, wet brake system, final drive, transmission and differential.

### Features and Benefits

- Meets API GL-4 gear oil performance
- Maintains viscosity under severe service conditions
- Friction modifiers for superior wet brake chatter control
- Outstanding wear protection for gears and hydraulic systems

### Applications

- AGCO Power Fluid 821XL
- Allison C-4
- API GL-4
- CAT TO-2
- Case MS 1205, 1206, 1207, 1209, 1210
- Case New Holland: MAT 3525
- Denison HF-0, HF-1, HF-2
- Eaton Vickers I-286-S, M-2950-S
- Ford New Holland ESN-M2C134-D
- FNHA 2C 201
- John Deere J20C
- Kubota UDT
- Massey Ferguson M-1135, M-1141, M-1143, M-1145
- Volvo WB101
- White Q-1826
- ZF TE-ML-03E, -05, -06



1-800-566-4853



East Greenbush, NY



[www.nu-tierbrands.com](http://www.nu-tierbrands.com)





LUBRICANTS



# Product Data Sheet

## Typical Properties

Product Code	Test Method	331965
Viscosity, cSt @ 40°C	ASTM D-445	60.4
Viscosity, cSt @ 100°C	ASTM D-445	9.7
Viscosity Index	ASTM D-2270	146
Brookfield Viscosity, cP @ -34.4°C	ASTM D-2983	45,000
KRL Shear Testing after 20 hrs / visc. cSt @100°C	CEC-L-45-T-93	8.2
Color	ASTM D-1500	L3.5
Pour Point, °F	ASTM D-5949	-43
Flash Point, COC, °F	ASTM D-92	410
Gravity, API	ASTM D-4052	29.8

Note: Refer to equipment owner's manual for proper lubricant recommendation

Rev. 05/21



1-800-566-4853



East Greenbush, NY



[www.nu-tierbrands.com](http://www.nu-tierbrands.com)

