



LUBRICANTS

Product Data Sheet

Transcrest® Multi-Purpose ATF

Automatic Transmission Fluid

High quality automatic transmission fluid suitable for many passenger car and heavy duty automatic transmissions. It is designed for use in electronic and hydraulic controlled transmissions and can also be used in certain other applications such as power steering units, rotary screw compressors, and some hydraulic fluid applications.

Features and Benefits

- Red color for easy identification
- Outstanding oxidation resistance
- Dependable anti-wear protection
- Low temperature performance providing outstanding cold start shifting

Applications

- Pre-2006 model General Motors automatic transmissions where **DEXRON® III** fluid is specified
- Post-1981 and pre-2007 Ford automatic transmissions where a now obsolete **MERCON®** fluid is specified
- Where Allison C-4 and Caterpillar TO-2 fluids are required
- Certain hydraulic and compressor systems

Typical Properties

Product Code	Test Method	332022
API Gravity	ASTM D-1298	32.8
Specific Gravity	ASTM D-4052	0.861
Viscosity, cSt @ 40°C	ASTM D-445	34.3
Viscosity, cSt @ 100°C	ASTM D-445	7.1
Viscosity Index (min)	ASTM D-2270	168
Brookfield Viscosity, cP @ -40°C	ASTM D-2983	17,250
Flash Point, °C (°F)	ASTM D-92	218 (424)
Pour Point, (°F)	ASTM D-5949	-46
Color	ASTM D-1500	Red

Note: Typical values shown are representative of current production and may vary within modest range. Always consult the equipment owner's manual for proper fluid selection.

Rev. 09/24



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

