



LUBRICANTS



Product Data Sheet

Cylinder Oil

Compounded steam cylinder oil

High quality “steam cylinder” and worm gear type lubricant. They are compounded with a special fatty oil that provides an excellent adhesion and lubrication under wet conditions encountered with saturated steam and compression of “wet” gas.

Features and Benefits

- Good thermal resistance and oxidation stability
- Effective lubrication and corrosion protection when subject to heavy steam-washing conditions

Applications

- Recommended for the lubrication of reciprocating steam engines over a wide range of saturated steam pressures and temperatures
- Lubricant for gas compressors having separate cylinder lubrication systems especially recommended under wet conditions
- Suitable for lubricating worm gear reducers (bronze to steel gear)
- Slow moving plain or antifriction type bearings
- Enclosed chain drives
- Certain low speed and enclosed gear drives

Typical Properties

ISO Grade	Test Method	460	680	1000
Product Code		334701	334703	334705
AGMA Number		7 Comp	8 Comp	8A Comp
Viscosity, cSt @ 40°C	ASTM D-445	450	680	1,000
Viscosity, cSt @ 100°C	ASTM D-445	29.5	37.5	45.0
Viscosity Index	ASTM D-2270	97	97	85
API Gravity	ASTM D-1298	27.1	22.1	21.6
Flash Point, COC, °F	ASTM D-92	510	535	>570
Pour Point, °F	ASTM D-97	15	20	32
Fatty Oil %		5	7	7

These properties are typical of current production, minor variations are to be expected in normal manufacturing.

Rev. 02/25



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

