



LUBRICANTS

# Gulfcut® NS18P Cutting Oil

## SDS - Safety Data Sheet

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier:** Gulfcut® NS18P  
**Other means of identification:** Metalworking Oil – Non-staining Neat  
**SDS Number:** 335000  
**CAS Number:** Blend  
**CHEMTREC:** EMERGENCY CONTACT 1-800-424-9300

**Supplier:**  
Nu-Tier Brands, Inc., Tulsa, OK  
Under License from Gulf Oil LP  
TECHNICAL CONTACT NUMBER: 918-550-8026, Ext. 507  
www.gulflubricants.net

### 2. HAZARDS IDENTIFICATION

**Classified Hazards**

**GHS Phrases:**  
H335 – May cause respiratory irritation

**GHS Precautionary Statements:**  
P273 – Avoid release to the environment  
P302+352 – IF ON SKIN: Wash with soap and water

**Hazard Statement:** May be fatal if swallowed and enters airways

This product contains hazardous material as defined by the OSHA Hazard Communication Standard CFR 1910.1200.

#### Label Elements



GHS Signal Word: WARNING  
GHS Classifications:  
Aspiration hazard; Category 1

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS	Concentration
Hydrotreated petroleum oil	Various	0-95%
Non-hazardous additives	Proprietary	5-10%

### 4. FIRST AID MEASURES

**INHALATION FIRST AID:** If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

**SKIN CONTACT FIRST AID:** Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.

**EYE CONTACT FIRST AID:** Flush with water for several minutes. If effects occur, consult a physician.

**INGESTION FIRST AID:** Rinse mouth with water. If symptoms develop, obtain medical attention.



# Gulfcut<sup>®</sup> NS18P Cutting Oil

## SDS - Safety Data Sheet

### 5. FIREFIGHTING MEASURES

**NFPA 704 Hazard Class**

Health: 1      Flammability: 1      Instability: 0



0 (Minimal)  
1 (Slight)  
2 (Moderate)  
3 (Serious)  
4 (Severe)

**Flash Point:** 187°C (370°F)  
**Flash Point Method:** COC

**Extinguishing Media:** Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F/100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

**Specific hazards arising from the chemical:**

**Unusual Fire & Explosion Hazards:** This material may burn, but will not ignite readily. If container is not properly cooled, it can rupture in the heat of a fire.

**Hazardous Combustion Products:** Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of sulfur, nitrogen or phosphorus may also be formed.

**Special protective actions for firefighters:** For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8).

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

### 6. ACCIDENTAL RELEASE MEASURES

**SAFEGUARDS (PERSONNEL):**

Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

**INITIAL CONTAINMENT:**

Absorb spills with inert material. Do not allow material to enter soil or surface water.

**LARGE SPILLS PROCEDURE:**

Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Do not flush to sewer.

**SMALL SPILLS PROCEDURE:**

Absorb spills with inert material.

**MISCELLANEOUS:**

Treat or dispose of in accordance with all federal, state, and local requirements. Incineration is preferred.

### 7. HANDLING AND STORAGE

**HANDLING (PERSONNEL):**



# Gulfcut<sup>®</sup> NS18P Cutting Oil

## SDS - Safety Data Sheet

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner, or properly disposed of. Wash hands thoroughly after handling.

### HANDLING (PHYSICAL ASPECTS):

Secure container after each use. Store in a cool dry area.  
Avoid contact with strong oxidizing agents.

### STORAGE PRECAUTIONS:

Store in a cool dry place, in a tightly closed container. Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### OCCUPATIONAL EXPOSURE LIMITS

Material	Source	Type	mg/m <sup>3</sup>
Oil Mist, Mineral	ACGIH TLV	TWA	5 mg/m <sup>3</sup>
Oil Mist, Mineral	ACGIH TLV	STEL	10 mg/m <sup>3</sup>
Oil Mist, Mineral	OSHA PEL	TWA	5 mg/m <sup>3</sup>
Oil Mist, Mineral	NIOSH REL	TWA	5 mg/m <sup>3</sup>
Oil Mist, Mineral	NIOSH REL	STEL	10 mg/m <sup>3</sup>

### ENGINEERING CONTROLS:

Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. TLV for mineral oil is 5 mg/cubic meter.

### EYE / FACE PROTECTION REQUIREMENTS:

When splashing of the material may occur, chemical goggles and/or a face shield are recommended.

### SKIN PROTECTION REQUIREMENTS:

Where contact is likely, wear chemical resistant gloves.

### RESPIRATORY PROTECTION REQUIREMENTS:

Under normal use conditions, with adequate ventilation, no special handling equipment is required. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

### GENERAL COMMENTS:

Always observe good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, etc...

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Note:** Data represents typical values and are not intended to be specifications.



# Gulfcut<sup>®</sup> NS18P Cutting Oil

## SDS - Safety Data Sheet

Appearance:	Light Amber	Flash Point:	374°F
Physical State:	Liquid	Density:	7.07 lb/gal approximately
Odor:	Petroleum	Solubility:	Nil in water
Viscosity:	18 cSt @ 40°F	Vapor Density:	Heavier than air (Air = 1)

### 10. STABILITY AND REACTIVITY

**REACTIVITY:** Not chemically reactive.

**CHEMICAL STABILITY:** Stable under normal ambient and anticipated conditions of use.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous reactions not anticipated.

**CONDITIONS TO AVOID:** Avoid all possible sources of ignition. Extended exposure to high temperatures can cause decomposition.

**INCOMPATIBLE MATERIALS:** Avoid contact with strong oxidizing agents and strong reducing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Not anticipated under normal conditions of use.

### 11. TOXICOLOGICAL INFORMATION

#### GENERAL INFORMATION:

Based on data on the components and the toxicology of similar materials

#### ROUTES OF ENTRY:

Skin, Eyes, Ingestion, and Inhalation.

#### ACUTE EXPOSURE:

#### EYE IRRITATION:

Not expected to cause eye irritation. Based on data from components or similar materials.  
Vapors may cause irritation.

#### SKIN IRRITATION:

Slightly irritating based on data from components or similar materials. Prolonged or repeated skin contact without proper hygiene may result in skin disorders such as acne.

#### RESPIRATORY IRRITATION:

Based on data from components and similar materials, Inhalation of vapors or mists may cause irritation.

#### DERMAL TOXICITY:

Expected to be of low toxicity: LD50 > 5000 mg/kg, Rabbit

#### ORAL TOXICITY:

Expected to be of low toxicity: LD50 > 5000 mg/kg, Rat

#### INHALATION TOXICITY:

Based on data from components and similar materials, product is not considered to be an inhalation hazard under normal conditions of use.

#### SENSITISATION:

Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components or similar formulations.

#### CHRONIC EXPOSURE:



# Gulfcut<sup>®</sup> NS18P Cutting Oil

## SDS - Safety Data Sheet

### CHRONIC TOXICITY:

No data available to indicate product or components present at greater than 1% are chronic health hazards.

### CARCINOGENICITY:

Product contains mineral and/or synthetic oils shown to be non-carcinogenic in laboratory studies with the same or similar materials. Mineral and synthetic oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.

### MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

### REPRODUCTIVE TOXICITY:

No data available to indicate either product or components present at greater than 0.1% that may cause reproductive toxicity.

### TERATOGENICITY:

No data available to indicate either product or components present at greater than 0.1% that may cause birth defects.

### ADDITIONAL INFORMATION:

No other health hazards known.

## 12. ECOLOGICAL INFORMATION

### ENVIRONMENTAL HAZARDS:

Ecological Toxicity data has not been determined specifically for this product. The ecological toxicity hazard is based on an evaluation of data for the components or a similar material. This material is expected to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

### ENVIRONMENTAL FATE:

This material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material. This product contains components which may be persistent in the environment.

## 13. DISPOSAL CONSIDERATIONS

### WASTE DISPOSAL:

Avoid disposal into waste water treatment facilities. Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements. This product, if discarded, is not considered a hazardous waste.

## 14. TRANSPORTATION INFORMATION

PRODUCT LABEL .....: Gulfcut<sup>®</sup> NS18P

D.O.T SHIPPING .....: Not Regulated by DOT.

IMDG: This material is not classified as dangerous under IMDG regulations.

IATA: This material is not classified as dangerous under IATA regulations.

TRANSPORT CANADA: This material is not classified as dangerous under Transport Canada regulations.

## 15. REGULATORY INFORMATION



# Gulfcut<sup>®</sup> NS18P Cutting Oil

## SDS - Safety Data Sheet

### OSHA Hazard Communication Standard:

The classification of this material is based on OSHA HCS 2012 criteria.

United States inventory (TSCA):	All components are listed or exempted.
Canada inventory:	All components are listed or exempted.
Europe inventory:	All components are listed or exempted.
Japan inventory (ENCS):	All components are listed or exempted.
Australia inventory (AICS):	All components are listed or exempted.
Korea inventory (KECI):	All components are listed or exempted.
China inventory (IECSC):	All components are listed or exempted.
Philippines inventory (PICCS):	All components are listed or exempted.

### 16. OTHER INFORMATION

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Nu-Tier Brands, Inc. The data on this sheet are related only to the specific material designated herein. Nu-Tier Brands, Inc. assumes no legal responsibility for use or reliance upon these data.

END OF MSDS

REASON FOR ISSUE .....: New  
APPROVAL DATE        October 21, 2021  
SUPERCEDES DATE .....: New  
PART NUMBER .....: 335000