



LUBRICANTS



# Product Data Sheet

## Gulfcut<sup>®</sup> Soluble Oil B

### *Water extendible, general-purpose metalworking coolant*

Conventional general-purpose cutting fluid designed to be readily mixed with water. This premium quality soluble oil is recommended for a wide range of metalworking applications including stamping, turning, cutting and grinding steels, drilling, boring and milling. It can also be used to machine aluminum and copper alloys. Contains a biocide to control anaerobic bacteria keeping systems free of objectionable odor and helps prevent bacterial growth.

### Features and Benefits

- Excellent cooling
- Non-foaming emulsion
- High lubricity
- Rust protection

### Applications

#### Recommended Dilutions:

- |                              |               |                     |                |
|------------------------------|---------------|---------------------|----------------|
| • Water hydraulics           | 1-3% emulsion | • Milling           | 5-10% emulsion |
| • Grinding                   | 2-3% emulsion | • Drilling & boring | 5-10% emulsion |
| • Short term rust protection | 2-4% emulsion | • Turning           | 5-10% emulsion |

### Typical Properties

Product Code	Test Method	335193
Viscosity, cSt @ 40°C	ASTM D-445	34.0
API Gravity	ASTM D-287	24.0
Pour Point, °C (°F)	ASTM D-97	-32 (-25)
pH @ 20:1 (5%)		9.0
Neat oil appearance		Clear amber
Emulsion appearance		Milky white

\*Refractometer Factor = 1.0

*These properties are typical of current production, minor variations are to be expected in normal manufacturing.*

Rev. 06/21



1-800-566-4853



Tulsa, OK 74133



[www.nu-tierbrands.com](http://www.nu-tierbrands.com)

