



LUBRICANTS



# Product Data Sheet

## No-Rust® WB

### Soluble waxy rust-proofing oil

Solvent-cutback, corrosion preventive compound which forms a thin and easily removable soft film after evaporation of solvent. It is engineered and designed to protect both ferrous and non-ferrous parts for long term indoor protection and during shipment. **Gulf No-Rust® WB** also offers exceptional undercover protection of exterior and interior surfaces of machinery instruments, bearings, etc. Its soft film cold application can be sprayed, brushed or dipped on.

### Features and Benefits

- Ease of application
- Excellent metal wetting properties
- High flash point solvent carrier
- Excellent water displacement properties

### Applications

- Exterior and interior surfaces of machinery instruments
- Bearings

### Typical Properties

Product Code	335375
Type of film	Soft Waxy
Color	Dark Red
Specific Gravity	0.8520
Density, lbs/gal	7.10
Flash Point, °F	177

*These properties are typical of current production, minor variations are to be expected in normal manufacturing.*

*\* The main factor affecting the life of this product is storage conditions. Exposure to extreme temperature changes and moisture will reduce the shelf life of this product i.e., don't leave in the sun with the lid off. Best to keep Gulf No-Rust WB sealed and unopened in its original container.*

Rev. 06/21



1-800-566-4853



Tulsa, OK 74133



[www.nu-tierbrands.com](http://www.nu-tierbrands.com)

