



LUBRICANTS



# Product Data Sheet

## EDM Super Fluid

### High Performance, Long Life, Synthetic EDM Fluid

Provides excellent performance in both low and high amperage applications. This outstanding full synthetic fluid exhibits excellence resistance to high temperature oxidation which provides prolonged product life. Due to the low viscosity of this premium fluid unwanted particles readily settle yielding high-quality finishes. With its relatively high flash point and non-corrosive traits this product is extremely operator friendly. Good for use on all ferrous metals, aluminum, brass and copper.

### Features and Benefits

- High flash point, Non-staining
- Low mild odor
- Easy removal and cleaning
- Low viscosity, Produces low smoke
- Rapidly dissipates heat
- Finishes require little buffing

### Applications

- Discharge machines of all sizes
- Suitable for roughing operations

### Typical Properties

Property	Test Method	Result
Product Code		<b>335460</b>
Kinematic Viscosity, cSt @ 40°C	ASTM D-445	2.8
Viscosity, SUS @ 100°F	ASTM D-2161	35.3
Color, Saybolt	ASTM D156	30+
Flash Point, °F	ASTM D-92	>244°F (118°C)
Specific Gravity	ASTM D-4052	0.762
Density, lbs/gal	ASTM D-4052	6.35
Appearance		Clear and Bright

Note: Values shown are typical and do not constitute a specification. Minor variations in product are to be expected in normal manufacturing. Always confirm with the original manufacturer's recommendation for proper equipment operating requirements.

Rev. 06/21



1-800-566-4853



Tulsa, OK 74133



[www.nu-tierbrands.com](http://www.nu-tierbrands.com)

