



LUBRICANTS



Product Data Sheet

Gulf Form Oil

Economical, Readily Separates Forms from Concrete

Ready-to-use, non-staining concrete releasing agent that can be used on metal and wooden forms. It is formulated with light viscosity mineral oil and a unique additive system designed to prevent cement from adhering to form surfaces. **Gulf Form Oil** resists water wash-off while providing rust protection to metal forms. This product meets federal guidelines for VOC compliance and can be applied using a brush, spray, or roller application.

Features and Benefits

- Non-Staining
- Ready to Use
- Prevents Concrete Build Up on Forms
- Use on Metal, Plastic and Wood Forms
- Good Low Temperature Use
- Low VOC Content
- Prevents Rusting of Metal Forms
- Prevents Buildup of Concrete on Forms

Applications

Designed to impart easy of separation on wood, steel, aluminum, epoxy coated and other types of forms in both indoor and outdoor conditions. It may be easily applied with a roller, brush, or sprayer. The applied film should be uniform and completely wet the surface. For best results, this product should be applied to a clean, dry surface.

Typical Properties

Product Code	Test Method	335712
Viscosity, cSt @ 40°C	ASTM D445	17.5
Viscosity, cSt @ 100°C	ASTM D445	3.85
Viscosity Index	ASTM 2270	111
Pour Point, C° (F°)	ASTM 5946	-23 (-10°F)
Color	ASTM D1500	L1.0
Wetting Agent	Report	Present
Flash Point, COC, °F (°C)	ASTM D92	378 (192)
VOC content, U.S. EPA & State Requirements (g/l)	ASTM D3960	Meets (<30)
Density	ASTM D4052	7.11

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.

Rev. 11/22



1-800-566-4853



Tulsa, OK 74133



www.nu-tierbrands.com

