



LUBRICANTS



# Product Data Sheet

## Form Oil

### Economical Oil, Ready Separation of Forms from Concrete

Ready-to-use, non-staining concrete releasing agent that can be used on metal and wooden forms. It is formulated with light viscosity mineral oil and a unique additive system designed to prevent cement from adhering to form surfaces. **Gulf Form Oil** resists water wash-off while providing rust protection to metal forms. This product meets federal guidelines for VOC compliance and can be applied using a brush, spray or roller application.

### Features and Benefits

- Non-Staining
- Ready to Use
- Prevents Concrete Build Up on Forms
- Use on Metal, Plastic and Wood Forms
- Good Low Temperature Use
- Low VOC Content
- Prevents Rusting of Metal Forms
- Prevents Buildup of Concrete on Forms

### Applications

Designed to impart easy of separation on wood, steel, aluminum, epoxy coated and other types of forms in both indoor and outdoor conditions. It may be easily applied with a roller, brush, or sprayer. The applied film should be uniform and completely wet the surface. For best results, this product should be applied to a clean, dry surface.

### Typical Properties

Product Code	Test Method	335712
Viscosity, cSt @ 40°C	ASTM D445	17.5
Viscosity, cSt @ 100°C	ASTM D445	3.85
Viscosity Index	ASTM 2270	111
Pour Point, C° (F°)	ASTM 5946	-23 (-10°F)
Color	ASTM D1500	L1.0
Wetting Agent	Report	Present
Flash Point, COC, °F (°C)	ASTM D92	378 (192)
VOC content, U.S. EPA & State Requirements (g/l)	ASTM D3960	Meets (<30)
Density	ASTM D4052	7.11

*Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.*

Rev. 05/21



1-800-566-4853



Tulsa, OK 74133



[www.nu-tierbrands.com](http://www.nu-tierbrands.com)

