



LUBRICANTS



Product Data Sheet

HyWay

Hydraulic System and Way Lubrication

High quality lubricant designed for machines that utilize a combined hydraulic and slideway lubrication system. It has been uniquely formulated with a proprietary, noncorrosive additive system designed to enhance the essential property of adhesion and reduce stick-slip in horizontal and vertical way surfaces.

Features and Benefits

- Excellent water separation
- Reduction of friction and wear
- Exceptional rust, corrosion, and wear protection
- Lighter color to provide good visibility of slideways

Applications

- Slides and ways of planers, grinders, mills, lathes, screw machines, drilling machines, boring machines, and other tools / machines
- Bearings and gears of other machinery that require additional anti-wear protection

Typical Properties

ISO Viscosity Grade	Test Method	32	68	220
Product Code		336480	336482	336484
Viscosity, cSt @ 40°C	ASTM D-445	32.1	67.8	219
Viscosity, cSt @ 100°C	ASTM D-445	5.3	8.7	19.4
Viscosity Index	ASTM D-2270	100	100	100
Rust Characteristics	D-665A	Pass	Pass	Pass
Flash Point, COC, °F	ASTM D-92	403	425	510
Pour Point, °F	ASTM D-97	-5	-5	5
Copper Corrosion	ASTM D-130	1b	1b	1b

These properties are typical of current production, minor variations are to be expected in normal manufacturing.

Rev. 05/21



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

