



LUBRICANTS



# Product Data Sheet

## Gulfsyn FE 75W-85 Gear Oil

### Full synthetic, GL-5, fuel-efficient axle lubricant

Synthetic, extreme pressure, gear and bearing lubricant designed for use in many late model BMW, Dodge and Mercedes-Benz differentials where the OEM specifies a fuel efficient, low viscosity, GL-5 gear oil. **Gulfsyn FE 75W-85 Gear Oil** is formulated to provide outstanding protection for gears and bearings operating under a wide variety of load conditions and temperatures.

### Features and Benefits

- Non-foaming
- Improved fuel mileage
- Excellent demulsibility
- Extended drain potential
- Superior low-temperature performance
- Suitable for use in limited slip differentials

### Applications

- API Service GL-5 & MT-1
- MIL-L2105E
- GM 88862826
- Chrysler / Dodge / Jeep
- Toyota/Lexus Gear Oil LT
- MB 235.15 / 235.7 / 235.74
- BMW 83 12 0 445 868/BOT 448
- AUDI G052 513
- Ford WSS-M2C942-A

### Typical Properties

SAE Grade	Test Method	75W-85
Product Code		<b>337195</b>
API Service		GL-5/MT-1
Viscosity, cSt @ 40°C	ASTM D-445	70.5
Viscosity, cSt @ 100°C	ASTM D-445	12.8
Brookfield cP @-40°C	ASTM D-2983	33,130
Viscosity Index		185
Pour Point	ASTM D-97	-45°F
Foam Test	ASTM D-892	Pass
Copper Corrosion	ASTM D-130	Pass
FZG Scuffing Test, stages	ASTM D-5182	>12

These properties are typical of current production, minor variations are to be expected in normal manufacturing.

\*Always follow equipment manufacturer recommendations for appropriate viscosity grade.

Rev. 08/22



1-800-566-4853



Tulsa, OK 74133



www.nu-tierbrands.com

