



LUBRICANTS



Product Data Sheet

All Season Antifreeze 50/50 Premixed

Conventional, Green Coolant

Gulf All Season 50/50 Premixed Antifreeze & Coolant is a superior quality ethylene glycol-based engine coolant with a low silicate corrosion inhibitor package. This product protects coolant system metals, including heat-rejecting aluminum, against pitting caused by cavitation and corrosion. It provides protection against radiator freeze-up down to -35°F and boil over to 265°F (with a 15-psi radiator cap in good condition).

Gulf All Season 50/50 Premixed Antifreeze & Coolant is recommended for use in older model domestic and foreign cars and light duty trucks and will provide up to 50,000 miles or 2 years' service life when installed as initial fill, or after a complete flush and cleaning of a cooling system in reasonable condition. It is compatible with supplemental coolant additives (SCA) and coolant filters and thus can be used in heavy duty diesel coolant systems when pre-charged with SCA.

Gulf All Season 50/50 Premixed Antifreeze & Coolant / Product ID# 841112

- Approved for use in gasoline and diesel engines
- Protects all engine metals including aluminum
- Meets heavy duty standards for low silicate antifreeze
- 100% virgin ethylene glycol based
- Available as a concentrate
- With bittering agent

Features and Benefits

- Low silicate and aluminum compatible
- Protects against winter freezing and summer boil over
- Recommended for older model domestic and foreign cars and light duty trucks
- Prevents pitting caused by cavitation and corrosion of brass, copper, solder, steel, cast iron and aluminum

Approvals

- ASTM D 3306
- ASTM 4985
- Chrysler MS 7170
- Ford ESE-M97B44-A
- GM 1825M
- GM 1899M
- TMC RP 302B



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com





LUBRICANTS



Product Data Sheet

Typical Properties

Product ID: 841112	ASTM Test Method	Typical Specifications
Specific Gravity @ 60°F	D1122	1.070 – 1.090
pH, 50% V	D1287	10 - 11
Freeze point (°C/°F)	D1177	-37 / -34
Color	-	Green
Reserve Alkalinity, (mL)	D1121	3.4 min.
Silicon, ppm	D6130	250 Max
Bittering Agent	-	Yes
Chloride (ppm)	D3634	25 max.
Glycol Content (wt.%)	-	46 min.

Rev. 02/25



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

