

Product Bulletin

Gulfpride® Two Cycle Marine Engine Oil

TC-W3 Water Cooled 2-Cycle Engine Oil

Ashless, two-stroke (cycle) engine oil formulated with high-quality base oils and an ashless high temperature additive system designed to control deposits and protect engine parts from corrosion and wear. It is licensed by the National Marine Manufacturers Association (NMMA) as a TC-W3® oil having successfully surpassed all NMMA TC-W3® testing requirements.

Features and Benefits

- Blue tint for easy identification
- Reduces carbon and deposit build-up on engine parts
- Helps prevent piston and ring sticking
- Resists the formation of harmful gels and deposits during temporary storage
- Approved: TC-W3 Registration Number: RL-26642T

Applications

- All water-cooled 2-cycle engines requiring NMMA TC-W3
- Direct inject and pre-mix systems
- Outboard Marine Corporation (Johnson / Evinrude), Mercury, Chrysler, Kawasaki, Yamaha, and Suzuki, as well as other outboard marine engine manufacturers

Typical Properties

Product Code	Test Method	330501
Kinematic Viscosity, cSt at 40°C	ASTM D-445	56.3
Kinematic Viscosity, cSt at 100°C	ASTM D-445	9.1
Brookfield Viscosity @ -25°C, cP	ASTM D-2983	4,300
Sulfated Ash, Mass %	ASTM D-874	Nil
Pour Point	ASTM D-5949	-33°F
Color	Visual	Blue
Flash Point, (PM) °F	ASTM D-93	219°F

Rev. 01/22





