



ECOSE[®] Synthetic *EURO* Motor Oil

Full Synthetic - European Formula

Premium quality, full synthetic engine oil formulated to meet the high-performance requirements of most European passenger car manufacturers. It is recommended for use in passenger cars, light trucks, and sport utility vehicles operating under demanding driving conditions. **ECOSE[®] Full Synthetic EURO 5W-40** has been tested to provide optimal engine oil performance required for European and other high-performance gasoline, certain diesel and turbo charged engines.

Features and Benefits

- Ultimate protection against varnish and sludge
- Assist in lowering emissions
- Outstanding high temperature protection
- Extended oil drain intervals
- Synthetic base oil for added oxidation stability
- Improved volatility and low temperature properties

Applications

- Porsche A40, MB 226.5 / 229.3 / 229.5 and VW Standard 502 00 / 505 00
- Meets or exceeds newer European ACEA requirements of ACEA A3/B4-12
- Provides dependable performance for BMW Longlife-01, Audi, Opel GM-LL B-025
- Renault 710 / 700 and PSA B71 2296 (Peugeot) - for use in gasoline, diesel, and turbocharged engines

Typical Properties

SAE Grade	Test Method	5W-40
Product Code		530340
API Service		SN/CF
Kinematic Viscosity, cSt at 40°C	ASTM D-445	85.0
Kinematic Viscosity, cSt at 100°C	ASTM D-445	14.2
Viscosity Index, calculated		173
Cold Cranking at temp °C, cP	ASTM D-5293	5800 at -30°C
HT/HS Viscosity, cP	ASTM D-4683	3.9
Noack Volatility, %	ASTM D-5800	11

Note: Typical values shown are representative of current production and may vary within modest range.

Rev 12/22



877-771-5823



East Greenbush, NY



www.nu-tierbrands.com

