



Product Data Sheet

ECOSE[®] HIGH MILEAGE MOTOR OIL

HELPS To REMOVE ENGINE SLUDGE and REDUCE WEAR

High Mileage Motor Oil is specially designed for gasoline engine powered vehicles with 75,000 miles or more. This oil has proven to reduce high temperature varnish deposits and ring sticking and is an excellent choice for use in all seasons. All viscosity grades meet the requirements of API SP and the latest ILSAC GF-6A performance, as well as meeting the requirements of all previous API "S" categories, including SN Plus, SN, SM, and SL.

Features and Benefits

- Provides extra wear protection
- Excellent low temperature pumpability
- Provides extra cleaning to critical engine parts
- Condition seals and makes them less susceptible to leaking

Approvals

- API SP / ILSAC GF-6A
- Previous API "S" categories including SN Plus, SN, and SM

Applications

- Lower mileage vehicles, including new cars still under warranty
- Older mileage and rebuilt passenger cars, light duty trucks and SUVs

Typical Properties

SAE Grade		5W-20	5W-30	10W-30
Product Code	Test Method	530362	530364	530366
Gravity, API	ASTM D-4052	32.8	33.0	31.0
Kinematic Viscosity, cSt at 40°C	ASTM D-445	52.0	62.0	68.0
Kinematic Viscosity, cSt at 100°C	ASTM D-445	8.8	10.5	10.6
Viscosity Index, calculated		153	158	143
Pour Point °F	ASTM D-97	-43	-40	-35
Cold Cranking at temp °C, cP	ASTM D-5293	5800 @ -30	5900 @ -30	5400 @ -25
Color	ASTM D-1500	3.0	3.5	3.5
Flash Point (COC) °F	ASTM D-92	440	450	460
Chrysler MS-6395		Yes	Yes	Yes
Ford WSS-		M2C960-A1	M2C961-A1	

Note: Minor variations in product are to be expected in normal manufacturing. Always confirm with the original manufacturer's recommendation for proper equipment operating requirements.

Rev 12/22



877-771-5823



East Greenbush, NY



www.nu-tierbrands.com

