



## ECOSE® NZ HYDRAULIC OIL

### Ashless Zinc Free Hydraulic Oil

Premium non-zinc anti-wear hydraulic oil developed for high pressure, high output systems and other requirements where an ashless product is desired. They are designed for use in high pressure, high speed hydraulic pumps used in industrial and mobile hydraulic systems. This lubricant is recommended in applications where environmental or other considerations prevent the use of fluids containing heavy or near-heavy metals such as zinc. Full protection is provided for high pressure vane and piston pumps as well as gear type pumps.

### Features and Benefits

- Ashless, high thermal stability
- Outstanding hydrolytic stability
- Full antioxidant and anti-foam protection; low air entrainment
- Excellent rust and corrosion protection for all metal components
- Excellent anti-wear protection for pumps, motors, valves, and other hydraulic components

### Applications

- Denison HF-0, HF-1, HF-2
- Vickers I-286S, M-2952-S
- Cincinnati Milacron P-68, P-69, P-70
- US Steel 127, 136
- BF Goodrich 0152
- General Motors LH-04-1, LH-06-1, LH-03-1
- Lee Norse 100-1
- Ford M-6C32
- Air compressors
- Non-EP gear and bearing circulating oil systems

### Typical Properties

ISO Viscosity Grade	Test Method	32	46	68	100
Product Code		<b>534533</b>	<b>534546</b>	<b>534568</b>	<b>534570</b>
Viscosity, cSt @ 40°C	ASTM D-445	33.2	46.5	63.0	100
Viscosity, cSt @ 100°C	ASTM D-445	5.5	6.8	8.2	11.0
Viscosity Index	ASTM D-2270	101	100	96	98
Pour Point, °F (°C)	ASTM D-5949	-20 (-29)	-20 (-29)	-20 (-29)	-6 (-21)
Flash Point, °F (°C)	ASTM D-92	420 (216)	430 (221)	450 (232)	470 (240)
Oxidation Stability, hrs.	ASTM D-943	6,000+	6,000+	6,000+	4,000+

*These properties are typical of current production, minor variations are to be expected in normal manufacturing.*

Rev. 01/23



877-771-5823



East Greenbush, NY



[www.nu-tierbrands.com](http://www.nu-tierbrands.com)

